

AMERON INDUSTRIAL COATINGS DIVISION -- 742-732 -- 8010-00-298-2288

=====
Product Identification
=====

Product ID:742-732

MSDS Date:01/01/1985

FSC:8010

NIIN:00-298-2288

MSDS Number: BDWJB

=== Responsible Party ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Address:201 N BERRY ST

City:BREA

State:CA

ZIP:92621-3904

Country:US

Info Phone Num:714-529-4597

Emergency Phone Num:714-529-4597

CAGE:0986

9

=== Contractor Identification ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Address:201 N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904

Country:US

Phone:714-529-4597

CAGE:09869

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 40.0%

OSHA PEL:100 PPM

Ingred Name:LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR

1910.1025),(CRO3 CEILING 0.1 MG/M3)

CAS:7758-97-6

RTECS #:GB

2975000

Fraction by Wt: 0.95%

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0.05MG/M3(CR)A2;8990

=====
Hazards Identification
=====

Effects of Overexposure:INHALE:ANESTHETIC, IRRITATION TO AIRWAY, & IF SKIN/EYE CONTACT,HEADACHE, DIZZINESS,COMA

=====
First Aid Measures
=====

First Aid:INCASE OF CONTACT,FLUSH SKIN AND EYES WITH PLENTY OF WATER WHILE REMOVING CONTAMINATED CLOTHING.IF INHALED,REMOVE TO FRESH AIR.CALL A PHYSICIAN IF SYMPTOMS PERSIST

=====
Fire Fighting Measures
=====

Flash Point:85F,29C TCC

Lower Limits:1.1

Extinguishing Media:CARBON DIOXIDE/DRY CHEMICAL-SMALL;POLYMER FOAM-LARGE FIRE

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS AVAILABLE FOR FIREMEN

Unusual Fire/Explosion Hazard:CLSOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE DUE TO PRESSURE BUILD UP

=====
Accidental Release Measures
=====

Spill Release Procedures:

REMOVE ALL SOURCES OF IGNITION(FLAMES,HOT SURFACES, & ELECTRICAL,STATIC, OR FRICTIONAL SPARKS).AVOID BREATHING VAPORS.VENTILATE AREA .REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS ONE FLAMMABLE (OR COMBUSTIBLE) LIQUID

Other Precautions:DO NOT TAKE INTERNA

LLY,CONTAINERS SHOULD BE GROUNDED

WHEN POURING,AVOID FREE FALL IN EXCESS OF A FEW INCHES,DO NOT FLAME
CUT,BRAZE, OR WELD COATED MATERIAL WITHOUT VENTILATION

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED BUREAU OF MINES RESPIRATORS W/PROPER
FILTER OR HOOD

Ventilation:GENERAL DILUTION/LOCAL EXHAUST FOR TLV&LEL SAFETY&WELDING

Protective Gloves:ALOT OF CONTACT

Eye Protection:USE EYEWEAR IF SPLASHING

Other Protective Equipment:PREVEN

T PROLONGED SKIN CONTACT TO

CONTAMINATED CLOTHING

Supplemental Safety and Health

BP 155-189C PBCR04 AOT-LD50; 10(GM/KG)

=====
===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:311-373F

Evaporation Rate & Reference:< ETHER

Percent Volatiles by Volume:58.7

=====
===== Stability and Reactivity Data =====

Stability Condition to Avoid:FIRES,HEAT & HOT SURFACES

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL,STATE, AND
FEDERAL REGULATIONS.INCINERATE IN APPROVED FACILITY.DO NOT
INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utili

zing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.