View NSN Online: https://aerobasegroup.de/nsn/8010-00-298-2295

PRAXAIR INC -- ENAMEL ALKYD GLOSS GREEN 14064 -- 8010-00-298-2295

Product ID: ENAMEL ALKYD GLOSS GREEN 14064 MSDS Date:01/01/1987 FSC:8010 NIIN:00-298-2295 **MSDS Number: BDWJS** === Responsible Party === **Company Name: PRAXAIR INC** Address:39 OLD RIDGEBURY RD Box:2153 City:DANBURY State:CT ZIP:06817-0001 Country:US Info Phone Num:203-794-5782 Emergency Phone Num:203-794 -5782 CAGE:0LV01 === Contractor Identification === Company Name: PRATT AND LAMBERT INC Box:6027 City:CLEVELAND State:OH ZIP:44101-1027 Country:US Phone:216-566-2902 CAGE:61196 Company Name: PRAXAIR, INC. Address:39 OLD RIDGEBURY RD Box:City:DANBURY State:CT ZIP:06810-5113 Country:US Phone:800-772-9247; 800-PRAXAIR CAGE:0LV01

Ingred Name:*MINERAL SPIRITS CAS:64475-85-0 RTECS #:PY8240000 ACGIH TLV:100PPM

Ingred Name:XYLENES (O-,

M-,P- ISOMERS) (SARA III) CAS:1330-20-7 RTECS #:ZE2100000 OSHA PEL:100 PPM/150 STEL ACGIH TLV:100 PPM/150STEL;9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:IRON OXIDE CAS:1332-37-2 RTECS #:NO7380000

Ingred Name:CARBON BLACK CAS:1333-86-4 RTECS #:FF5800000 OSHA PEL:3.5 MG/M3 ACGIH TLV:3.5 MG/M3; 9192

Effects of Overexposure:MATRL INTO LUNGS CAN CAUSE CHEM PNEUMONITIS WHICH CAN BE FATAL.INHAL:NAUSEA,UNCONSCIO US,EVN ASPHYXIA

First Aid:SWALLOWED:INDUC VOMIT IMMED.GIVNG 2 GLASES OF WATER & STICKING FINGER DOWN THROAT.CONSULT DR OR POISON CONTROL CENTR IMMED.(NVR GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.)INHAL:REMOV TO FRESH AI R IMMED.IF BREATH HAS STOP,GIVE ARTIF RESPIRATION

Flash Point:80F,27C Extinguishing Media:CL B FIRE EXTING(CO*2,ALL PURPOS DRY CHEM OR ALCOH FOAM) Fire Fighting Procedures:FIREFIGHTERS SHOULD WEAR SELF-CONTND BREATHING APPARATUS.

Unusual Fire/Explosion Hazard: KP CONTNRS TIGHTLY CLOS. ISOLAT FR HEAT, ELECT EQPMT, SPARKS & FLAME CLOS CONTNRS MAY EXPLOD EXPOS(SUP)

Spill Release Procedures: KEEP SPECTATORS AWAY.ELIM ALL IGNIT SOURCES (FLAMES, HOT SURFACES & SOURCES OF ELECTR, STATIC OR FRICTIONAL SPARKS).DIKE & CONTN SPILL W/INER T MATRL (E.G.SAND,EARTH).TRANSFER LIQDS TO COVERED METAL CONT NRS F/RECOVERY OR DISPOS,OR REMOV INERTABSOBR.

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LG QUANTITIES IN COMPLIANCE W/OSHA 29CFR1910.106. Other Precautions:DO NOT TAKE INTERNALLY.CLOSE CONTNR AFTER EACH USE.

Respiratory Protection:USE NIOSH APPRVD MECH FILTR RESPI R TO REMOV OVRSPRAY. Ventilation:PROVID GEN DILUT & LOC EXHAUST VENTIL IN SUFFICIENT VOLUME Protective Gloves:SOLVNT IMPER ME Eye Protection:SAFETY SPECTACLES W/SIDE Other Protective Equipment:NOT LIKELY TO BE NEEDED. Supplemental Safety and Health *INDICATES SOLVENT. UNUS. FIRE & EXPLOS. HAZ: TO EXTREME HEAT. HAZARDOUS DECOMP PRODUCTS: AND CO*2.

HCC:F3 Boiling Pt:B.P. Text:193-395F Vapor Density:HEAV Evaporation Rate & amp; Reference:SLOWER THAN ETHER Percent Volatiles by Volume:61

Stability Indicator/Materials to Avoid:YES STRONG ACIDS OR ALKALINE MATERIALS Stability Condition to Avoid:NONE KNOWN Hazardous Decomposition Products:BURNING,INCLD WHN HEAT BY WELD,CUTTNG,WILL PRODUC SMOK CO(SU

Waste Disposal Methods:DISPOS IN ACCORD W/FED,STATE & LOC LAWS.INCINERATE

ONLY IN EPA PERMITTED FACILITY.DO NOT INCIN CLOS CONTNRS.OBSERV PRECAUTIONS F/DISPOS OF FLAMMBL MATRLS.CONTAMINATED ABSORBANT MAY BE DISPOS IN A HAZ WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any pers on utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.