View NSN Online: https://aerobasegroup.de/nsn/9150-00-322-9367

EXXON CO USA, A DIV OF EXXON CORP. -- ISOPAR M ;PRODUCT CODE:133468-00635 · 9150-00-322-9367

Product ID: ISOPAR M ; PRODUCT CODE: 133468-00635 MSDS Date:04/20/1990 FSC:9150 NIIN:00-322-9367 MSDS Number: BDWSZ === Responsible Party === Company Name: EXXON CO USA, A DIV OF EXXON CORP. Address:800 BELL ST Box:2180 **City:HOUSTON** State:TX ZIP:77252-2180 Country:US Info Ph one Num:713-656-3424 OR 713-656-2443 Emergency Phone Num:713-656-2443 OR 713-656-3424 CAGE:29700 === Contractor Identification === Company Name: EXXON COMPANY U.S.A. Box:2180 City:HOUSTON State:TX ZIP:77252-2180 Country:US Phone:713-656-5949 / 713-656-3424 CAGE:29700 Company Name: TEXPAR ENERGY INC. CAGE:0ANE5

Ingred Name:HYDROTREATED HEAVY NAPHTHA (IT CONSISTS PREDOMINANTLY OF C\*12-C\*15 ISOPARAFFINIC HYDROCARBONS.) CAS:647 42-48-9 Fraction by Wt: 100.0% Other REC Limits:NONE SPECIFIED OSHA PEL:5 MG/M3 AS OIL MIST ACGIH TLV:5 MG/M3 AS OIL MIST

LD50 LC50 Mixture:LD50 (ORAL RAT) IS >5G/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE:IRRITATION OF EYES,SKIN,RESPIRATORY OR G.I.TRACTS;CNS EFFECTS LIKE HEADACHE,DIZZINESS,NAUSEA,VOMITING AND POSSIBLE UNCONSCIOUSNESS;REDNESS OR BURNS OF EYES/SKIN POSSIBLE.CHRONIC:DRYING OF SKIN,D EFATTING OR DERMATITIS. Explanation of Carcinogenicity:DATA PER MSDS Effects of Overexposure:SEE HEALTH HAZARDS DATA. Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS OR WITH A PRE-EXISTING DISEASE INVOLVING THE EYES, SKIN, OR RESPIRATORY TRACT MAY BE AT INCREASED RISK FROM EXPOSURE.

First Aid:INHALAT

ION:REMOVE TO FRESH AIR. RESUSCITATE IF NOT BREATHING. GET MEDICAL ATTENTION. EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN:REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL ADVICE. INGESTION:DO NOT INDUCE VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE MEDICAL ATTENTION.

Flash Point Method:PMCC
Flash Point:160F,71C
Autoignition Temp:Autoignition Temp Text:460F
Lower Limits:0.6
Upper Limits:7.0
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. CONTAIN RUNOFF.
Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS. Spill Release Procedures: ELIM ALL IGNITION SOURCES. KEEP PEOPLE AWAY. RECOVER FREE PRODUCT. ADD SAND OR OTHER ABSORBENT TO SPILL AREA. VENT AREA. KEEP PRODUCT OUT OF SEWER & WATERCOURSES. AVOID SKIN CONTACT & INHAL OF VAPORS. Neutralizing Agent: NOT APPLICABLE.

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA. KEEP CO

NTAINERS TIGHTLY CLOSED WHEN NOT IN USE. PROTECT CONTAINERS FROM PHYSICAL DAMAGE.

Other Precautions:DO NOT TAKE INTERNALLY. DO NOT BREATHE MIST. AVOID PROLONGED OR REPEATED BREATHING OF VAPOR. AVOID CONTACT WITH EYES. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST AS REQUIRED IF ABOVE PEL/TLV.

Ventilation:LOCAL/GEN

ERAL TO MAINTAIN PEL/TLV.

Protective Gloves: NEOPRENE, NITRILE, OR NATURAL RUBBER

Eye Protection: SAFETY GOGGLES WITH OPTIONAL FACE SHIELD

Other Protective Equipment: EYE WASH STATION AND SAFETY SHOWER, WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO NOT BR

EATHE VAPORS OR MISTS.

HCC:V4 Boiling Pt:B.P. Text:401F,205C Vapor Pres:5 Spec Gravity:0.79 pH:NEUTRL Viscosity:2.46 CP @25C Evaporation Rate & amp; Reference: