View NSN Online: https://aerobasegroup.de/nsn/6810-00-348-9542 CHASE CHEMICAL CO, INC -- MURIATIC ACID, 20 BE -- 6810-00-348-9542 ============= Product Identification ======================== Product ID:MURIATIC ACID, 20 BE MSDS Date:01/01/1985 FSC:6810 NIIN:00-348-9542 MSDS Number: BDWYQ === Responsible Party === Company Name: CHASE CHEMICAL CO, INC Address:13546 DESMOND ST City:PACOIMA State:CA ZIP:91331-2315 Country:US CAGE:8P578 === Contractor Identification === Company Name: CHASE C **HEMICAL CO INC** Address:13546 DESMOND ST Box:City:PACOIMA State:CA ZIP:91331-2315 Country:US CAGE:8P578 ====== Composition/Information on Ingredients ======== Ingred Name: HYDROGEN CHLORIDE (HYDROCHLORIC ACID) (SARA III) CAS:7647-01-0 RTECS #:MW4025000 Fraction by Wt: 31.4% OSHA PEL:C 5 PPM ACGIH TLV:C 5 PPM; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name:WATER

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 68.5%

===== Hazards Identification =====

Effects of Overexposure:EYE/SKIN: IRRIT OR BURNS. VAPORS: CHOKING. INGESTION: INTERNAL BURNS & BE FATAL.
======================================
First Aid:EYE: FLUSH WITH WATER 15 MIN,GET MED ATTN. SKIN: FLUSH WITH WATER,GET MED ATTN. INHALATION: REMOVE FROM EXPOSURE GET MED ATTN. INGESTION: DRINK LARGE AMOUNTS OF WATER,GET MED ATTN.
============ Fire Fighting Measures ============
Fire Fighting Procedures:SELF-CO NTAINED BREATHING APPARATUS Unusual Fire/Explosion Hazard:HYDROCHLORIC ACID REACTS WITH COMMON METALS TO PRODUCE HYDROGEN GAS WHICH IS FLAMMABLE/EXPLOSIVE
========= Accidental Release Measures ==========
Spill Release Procedures:FLUSH SPILL WITH LOTS OF WATER. NEUTRALIZE RESIDUE WITH ALKALIES,SUCH AS SOAD ASH OR LIME. PROVIDE AMPLE VENTILATION AS NEUTRALIZATION WILL EVOLVE CARBON DIOXIDE GAS.
=========== Handling and Storage =============
H andling and Storage Precautions:STORE IN DRY WELL VENTILATED AREA AWAY FROM HEAT & SUN. AVOID STORAGE WITH OXIDIZING SUBSTANCE. AVOID CONTACT WITH METALS. Other Precautions:UNNEUTRALIZED ACID MUST NOT CONTACT SULFIDES (SUCH AS SULFIED WASTES IN SEWERS) TO AVOID EVOLVING POISONOUS HYDROGEN SULFIDE GAS.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH EXPOSURE OF CONCERN Ventilation:LOCAL EXHAUST Protective Gloves:RUBBER/PLASTIC Eye Protection:CHEM SAFETY GOGGLES Other Protective Equipment:FACE SHIELD,RUBBER APRON,BOOTS & RUBBER CLOTH. SAFETY SHOWER Supplemental Safety and Health CONTAINER SIZE: 55 GAL DRUM
======================================
HCC:C1 Boiling Pt:B.P. Text:182F,83C Vapor Pres:20 Spec Gravity:1.16

Evaporation Rate & Description R

Percent Volatiles by Volume:100
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES MOST METALS,CHEMICALS,INC, ALKALIES & ORGANICS Hazardous Decomposition Products:HYDROGEN CHLORIDE GAS

Waste Disposal Methods: NEUTRALIZE WITH ALKALI AND FLUSH TO SEWER IF PERMITTED BY LOCAL, STATE & FEDERAL REGULATIONS.

========== Disposal Considerations ================

Disclaimer (provided with this information by the compiling agencies):

RP ACID ODOR.

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.