

BONDED PRODUCTS, INC. -- MIL-R-19907C,PART A PASTE REPAIR KIT(SUPDAT -- 2090-00-372-6064

=====
Product Identification
=====

Product ID:MIL-R-19907C,PART A PASTE REPAIR KIT(SUPDAT

MSDS Date:02/03/1986

FSC:2090

NIIN:00-372-6064

MSDS Number: BDXHS

=== Responsible Party ===

Company Name:BONDED PRODUCTS, INC.

Emergency Phone Num:215-696-9220

CAGE:DO082

=== Contractor Identification ===

Company Name:AB

BEY COLOR INC DBA ABBEY PRODUCTS AND BONDED

Address:400 E TIOGA ST

Box:City:PHILADELPHIA

State:PA

ZIP:19134-1127

Country:US

Phone:215-739-9960

CAGE:19092

Company Name:BONDED PRODUCTS, INC

Address:439 SOUTH BOLMAR STREET

Box:39

City:WEST CHESTER

State:PA

ZIP:19381-0039

Phone:610-696-9220 OR 215-739-9960

CAGE:DO082

=====
Composition/Information on Ingredients
=====

Ingred Name:DURAMITE

CAS:471-34-1

RTECS #:FF9335000

Fraction by Wt:

Other REC Limits:

OSHA PEL:

ACGIH TLV:

Ingr

ed Name:EPON 828
CAS:25068-38-6
RTECS #:SL6475000
Fraction by Wt:
Other REC Limits:
OSHA PEL:
ACGIH TLV:

Ingred Name:RESORCINOL (SARA III)
CAS:108-46-3
RTECS #:VG9625000
Fraction by Wt:
Other REC Limits:
OSHA PEL:10 PPM/20 STEL
ACGIH TLV:10 PPM/20 STEL; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:4-BUTANOLIDE
CAS:96-48-0
RTECS #:LU3500000
Fraction by Wt:
Other REC Limits:
OSHA PEL:
ACGIH TLV:

Ingred Name:ABESTOS
CAS:1331-21-4
Fraction by Wt:
Other REC Limits:
OSHA PEL:2.0FI
BERS/CC
ACGIH TLV:0.2 FIBERS/CC

Ingred Name:TITANIUM DIOXIDE
CAS:1317-80-2
Fraction by Wt:
Other REC Limits:N/K FP-N
OSHA PEL:N/K FP-N
ACGIH TLV:N/K FP-N

Ingred Name:CLAY
CAS:1332-58-7
Fraction by Wt:
Other REC Limits:30 MPPCF.
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:2 MG/M3 TDUST; 9293

Ingred Name:SILICA, AMORPHOUS, DUST
CAS:112945-52-5
RTECS #:VV7310000
Fraction by Wt:
Other REC Limits:.
OSHA PEL:6 MG/M3
ACGIH TLV:10 MG/M3; 8990

Ingred Name:SILICON DIOXIDE, AMORPHOUS
CAS:112945-52-5
RTECS #:V

V7310000
OSHA PEL:20 MPPCF
ACGIH TLV:10 MG/M3

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:SEE SIGNS & SYMPTOMS OF OVEREXPOSURE.
USER SHOULD CONSULT CURRENT PERMISSIBLE LEVELS OF EXPOSURE FOR
ASBESTOS.
Explanation of Carcinogenicity:ASBESTOS:IARC,HUMAN CARC GROUP
1.NPT:KNOWN TO BE CARC.OSHA:CANCER & LUNG DISEASE
HAZARD.ACGIH
CONFIRMED HUMAN CARC
Effects of Overexposure:PRIMARY IRRITATION TO SKIN ON PROLONGED OR
REPEATED CONTACT.CAN BE IRRIT TO EYES.CAN CAUSE HEADACHE ON
PROLONGED EXPOSURE.

===== First Aid Measures =====

First Aid:INHAL:REMOVE VICTIM TO FRESH AIR APPY ARTIFICAL RESP.IF
REQUIRED,GET MED .HELP SKIN:WASH THOROUGHLY W/ SOAP & H*20 OR
WATERLESS CLEANSER.IF IRRITATION PERSISTS GET MEDICAL
HELP.EYES:FLUSH W/ H*20 FOR AT LEAST 15
MINUTES.GET PHYS
ASST.INGEST:INDUCE VOMITING.IF CONSCIOUS GET MEDICAL ASSISTANCE
IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:> 240 F;115.56 C
Extinguishing Media:DRY CHEMICALS, CO*2, FOAM, WATER FOG.
Fire Fighting Procedures:KEEP FIRE EXPOSED CONTAINERS.COOL W/ WATER
SPRAY. WEAR SCBA.
Unusual Fire/Explosion Hazard:HANDLE PRODUCT AS A COMBUSTIBLE MATERIAL
WHEN EXPOSED TO BURNING OR FIRE.

=====

Accidental Release Measures =====

Spill Release Procedures:WEAR APPROVED RESP EQUIPMENT & NECESSARY EQUIP TO PROTECT FROM SKIN & EYE CONTACT.SHOVEL OR SCRAPE INTO SALVAGE DRUMS.SOAK UP RESIDUE W/ ABSORBENT MATERIAL SUCH AS CLAY & PLACE INTO TIGHT CONTR.GUARD AGAINST FIRE HAZ & REMOVE SOURCES OF IGNITION.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN TIGHTLY CLOSED CONTAINERS,USE ONLY W/ THE AP
PROVED CURING AGENT.WASH EXPOSED SKIN AREAS.AFTER HANDLING.STORE IN A COOL DRY AREA.

Other Precautions:REMOVE CONTAMINATED CLOTHING & LAUNDRER BEFORE REUSE.DESTROY CONTAMINATED SHOES & OTHER LEATHER ARTICLES.USE RUBBER GARMENTS.AVOID CONTACT W/ EYES,SKIN CLOTHING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED RESPIRATOR EQUIP.AS REQUIRED TO PREVENT VAPOR EXPOSURE(MFR).NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR E
XPOSURE OF CONCERN

Ventilation:LOCAL EXHAUST APPLICATION AS NEEDED TO CONTROL VAPOR EXPOS FROM OPERATOR.MECHANICAL RECOMMENDED.

Protective Gloves:RUBBER OR IMPERVIOUS

Eye Protection:CHEMICAL WORKERS GOGGLES,FACESHLD OPTION

Other Protective Equipment:IMPERVIOUS RUBBER GARMENTS,SAFETY SRRAY OR SHOWER & EYE BATH

Work Hygienic Practices:OBSERVE GOOD WORK HYGIENIC PRACTICES.

Supplemental Safety and Health

PART NO:REINFORCED PLASTI LAMINATE-BOAT KIT). KEY1:N1.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:ND MFR

Vapor Pres:NO (MFR)

Solubility in Water:VERY SLIGHT

Appearance and Odor:WHITE PASTE W/ A CHARACTERISTIC ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING AGENTS AGENTS AND MINERAL ACIDS.

Stability Condition to Avoid:OXIDIZING AGENTS AND ACIDS AND HIGH TEMPERATURES

Hazardous Decomposition Products:CARBON MONOXIDE,CARBON DIOXIDE AND SMOKE,.

===== Disposal Considerations =====

Waste Disposal Methods: BURN IN AN APPROVED CHEMICAL INCINERATOR OR BURY IN AN APPROVED LANDFILL THAT MEETS FEDERAL, STATE, & LOCAL POLLUTION REGULATIONS & ORDINANCES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.