

NAZ-DAR COMPANY -- BASE FLAT POSTER INK,PRODUCT CODE:5530 -- 8010-00-377-0735
===== Product Identification =====

Product ID:BASE FLAT POSTER INK,PRODUCT CODE:5530

MSDS Date:01/01/1987

FSC:8010

NIIN:00-377-0735

MSDS Number: BDXJH

=== Responsible Party ===

Company Name:NAZ-DAR COMPANY

Address:1087 N NORTH BRANCH ST

City:CHICAGO

State:IL

ZIP:60622-4234

Country:US

CAGE:EO327

=== Contractor Identification ===

Company Name:NAZ-DAR COMPANY

Address:1087 N NORTH BRANCH ST

Box:City:CHICAGO

State:IL

ZIP:60622

Country:US

Phone:312-943-8338

CAGE:EO327

Company Name:NAZDAR COMPANY

Address:1087 N NORTH BRANCH ST

Box:City:CHICAGO

State:IL

ZIP:60622-4292

Country:US

Phone:312-943-8338;800-736-7636

CAGE:76708

===== Composition/Information on Ingredients =====

Ingred Name:RULE-66 MINERAL SPIRITS (ALIPHATIC PETROLEUM DISTILLATE)

Fraction by Wt: 78.0%

ACGIH TLV:200 PPM (MFR)

Ingred Name:H

I-SOL 10 (AROMATIC PETROLEUM DISTILLATE)

Fraction by Wt: 8.0%

ACGIH TLV:100 PPM (MFR)

===== Hazards Identification =====

Effects of Overexposure:INHAL:ANESTHETIC,IRRITATION TO RESPIR.TRACT,CNS
DEPR,HEADACHE,DIZINESS.SKIN&EYES:PRIMARY IRRITATION.

===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF
NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE MOUTH;
GET MEDICAL AT
TENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER
SYMPTOMS OF OVEREXPOSURE.

===== Fire Fighting Measures =====

Flash Point:105F (T.C.C.)

Lower Limits:1.0

Extinguishing Media:FOAM,CO*2,DRY CHEMICAL

Fire Fighting Procedures:USE NIOSH APPROVED RESPIRATOR (SCBA) FOR FIRE
FIGHTING

Unusual Fire/Explosion Hazard:MAY EXPLODE UNDER EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:USE PERSONAL PROTECTIVE
EQUIPMENT.REMOVE ALL
IGNITION SOURCES.AVOID BREATHING VAPORS.VENTILATE AREA.REMOVE WITH
INERT,ABSORBENT AND NON-SPARKING TOOLS.FOLLOW PROCEDURES FOR
REPORTING SPILL IF REQUIRED

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LARGE
QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF CLASS II
COMBUSTIBLE LIQUIDS.

Other Precautions:DO NOT TAKE INTERNALLY.AVOID SKIN AND EYE CONTACT.DO
NOT BREATHE

E VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MESA APPR SCBA/AIR SUPP RESPIR.
Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN 1.0
Spec Gravity:0.81
Evaporation Rate & Reference:SLOWER THAN ETHER
Appearance and Odor:BASE FLAT POSTER INK
Percent Volatiles by Volume:89.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:WHEN H
EATED TO DECOMPOSITION,MAY GIVE
CO & OXIDES OF NITROGN

===== Disposal Considerations =====

Waste Disposal Methods:CONSULT LOCAL AUTHORITIES FOR DISPOSAL.DISPOSAL
MUST BE IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied
, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.