

GOODYEAR TIRE AND RUBBER CO -- 5071-C, PART 2 -- 8040-00-390-5606

=====
Product Identification
=====

Product ID:5071-C, PART 2

MSDS Date:01/01/1985

FSC:8040

NIIN:00-390-5606

MSDS Number: BDXKH

=== Responsible Party ===

Company Name:GOODYEAR TIRE AND RUBBER CO

Address:1144 E MARKET ST

City:AKRON

State:OH

ZIP:44316-0001

Country:US

Info Phone Num:216-796-2121 / FAX 216-796-1311

Emergency Phone Num:2

16-796-2121

CAGE:73842

=== Contractor Identification ===

Company Name:GOODYEAR TIRE AND RUBBER CO

Address:1144 E MARKET ST

Box:City:AKRON

State:OH

ZIP:44316-0001

Country:US

Phone:330-796-1906/613-996-66669(CANADA)

CAGE:73842

=====
Composition/Information on Ingredients
=====

Ingred Name:CATALYST

Fraction by Wt: 5.0%

ACGIH TLV:NONE

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 65.0%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:

1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL ALCOHOL (ETHANOL)
CAS:64-17-5
RTECS #:KQ6300000
Fraction by Wt: 30.0%
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM; 9192

=====
Hazards Identification
=====

Effects of Overexposure:FATIGUE, HDACHE, INCOORD, NAUSEA, UNCON

=====
First Aid Measures
=====

First Aid:REMOVE TO FRESH AIR. CNTCT MD.

=====
Fire Fighting Measures
=====

Flash Point:44F CC

L

ower Limits:1.27

Upper Limits:7.0

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, DRY CHEM, FOAM

=====
Accidental Release Measures
=====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. PREVENT
FROM ENTERING STREAMS & SEWERS.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP AWAY FROM SPARKS OR OPEN FLAME,
USE ADEQUATE VENT. AVOID BRTHNG VAPORS, SKIN/EYE CNTCT.

=====
Exposure Con
trols/Personal Protection
=====

Respiratory Protection:NOT REQ IF BELOW TLV, OTHERWISE DETERMINE IAW
CONC

Ventilation:EXHST TO KEEP BELOW TLV

Protective Gloves:YES

Eye Protection:YES

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:F2

Boiling Pt:B.P. Text:231F

Vapor Pres:28

Vapor Density:3.2

Spec Gravity:0.85

Evaporation Rate & Reference:240

Solubility in Water:SLIGHTLY

Appearance and Odor:YELLOW LIQ, AROMATIC

Percent Vol

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:IAW LOCAL, STATE, FED REG

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of Ame

rica in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.