

FILTRON CO INC -- FA9841 -- 5915-00-400-0844

===== Product Identification =====

Product ID:FA9841  
MSDS Date:01/01/1985  
FSC:5915  
NIIN:00-400-0844  
MSDS Number: BDXPF  
=== Responsible Party ===  
Company Name:FILTRON CO INC  
Address:148 SWEET HOLLOW RD  
City:OLD BETHPAGE  
State:NY  
ZIP:11804-1315  
Country:US  
Emergency Phone Num:914-699-2000  
CAGE:81831

=== Contractor Identification ===

Company Name:FILTRON CO  
INC  
Address:148 SWEET HOLLOW RD  
Box:City:OLD BETHPAGE  
State:NY  
ZIP:11804-1315  
Country:US  
Phone:914-699-2000  
CAGE:81831

===== Composition/Information on Ingredients =====

Ingred Name:POLYCHLORINATED BIPHENYLS (PCBS) (SARA III)  
CAS:1336-36-3  
RTECS #:TQ1350000  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

===== Hazards Identification =====

Effects of Overexposure:INHAL:RESP TK IRRIT.  
SKIN/EYE;IRRIT,INFLAM,CHLORACNE; MAY CAUSE LIVER DAMAGE

=====

===== First Aid Measures =====

First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR; IF BRTHNG DIFF,GIVE OXYGEN. EYE:IMMED FLUSH W/PLENTY OF WATER. SKIN: WASH W/SOAP&WATER. RMV CONTAM CLTHNG&SHOES. INGEST:INDUCE VOMIT. RPT UNTIL VOMIT IS CLEAR. NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATT

===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:EXTINGUISH W. AGENT SUITABLE FOR SURROUNDING FIRE.

Fire F

ighting Procedures:WEAR CHEMICAL PROTECTIVE SUIT WITH SELF CONTD BRTHG APP.

Unusual Fire/Explosion Hazard:MATL IS NON-FLAMMABLE BUT MAY GENERATE TOXIC GASES IN HEAT OF FIRE

===== Accidental Release Measures =====

Spill Release Procedures:EVAC NON-ESSENTL PERSONNEL. VENT SPIL AREA. WEAR PROTECT EQUIPT. STOP LEAK. SOAK UP LIQUID W/NON-REACTIVE MATL (SAND, DIRT, ETC) OR RMV BY DIKE & PUMPING OR OTHER SUITABLE MEANS. CLEAN AREA W/SUITABLE SAFETY SOL VENT. LAUNDER CONTAMINATED CLTHG.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED

Other Precautions:CHLORODIPHENYLS MAY ATTACK SOME TYPES OF RUBBER AND PLASTIC. DO NOT USE CONTAMINATED WORK CLOTHING. WASH/SHOWER AFTER EXPOSURE TO PCB'S.

===== Exposure Controls/Personal Protection =====

=====

Respiratory Protection:NIOSH/MESA APPR SCBA/AIR SUPP RESPIR.

Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV.

Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES/FACE SHIELD

Other Protective Equipment:WEAR FULL PROTECTIVE CLOTHING.

Supplemental Safety and Health

OVEREXPOS:CAN CAUSE FORMATION OF CYSTS.CAUSES STILLBIRTHS.IRRITATES EYES,NOSE,THROAT.

===== Physical/Chemical Properties =====

HCC:Z3

Solubility in Water:NEGLIGIBLE

Appearance and Odor:PALE YELLOW VI

SCOUS LIQUID W/HYDROCARBON ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: SEE OTHER PRECAUTIONS

Hazardous Decomposition Products: HYDROGEN CHLORIDE, CO, & OTHER  
TOXIC/IRRITATING GASES/FUMES.

===== Disposal Considerations =====

Waste Disposal Methods: CONTROLLED DISPOSAL REQD. GEN. V. HIGH TEMP  
INCINERATION. IAW ALL LOCAL, STATE, & FEDERAL REGULATIONS.

PERMITTED DISPOSAL OPERATOR REQUIRED.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.