

E.I. DU PONT DE NEMOURS & CO., INC. -- 70S, DUCO PRIMER, GRAY -- 8010-00-430-0193

=====  
Product Identification  
=====

Product ID:70S, DUCO PRIMER, GRAY

MSDS Date:01/01/1985

FSC:8010

NIIN:00-430-0193

MSDS Number: BDYQN

=== Responsible Party ===

Company Name:E.I. DU PONT DE NEMOURS & CO., INC.

Address:1007 MARKET STREET

Box:1635

City:WILMINGTON

State:DE

ZIP:19899

Country:US

Info Phone Num:800-441-751

5

Emergency Phone Num:800-441-7515

CAGE:18773

=== Contractor Identification ===

Company Name:E.I. DU PONT DE NEMOURS & CO., INC.

CAGE:18773

Company Name:E.I. DUPONT DE NEMOURS & CO

Address:1007 MARKET STREET

Box:City:WILMINGTON

State:DE

ZIP:19898

Country:US

Phone:800-441-7515;800-441-9442

CAGE:18873

=====  
Composition/Information on Ingredients  
=====

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)

CAS:67-56-1

RTECS #:PC1400000

Fraction by Wt: 3%

OSHA PEL:S,200PPM/250STEL

ACG

IH TLV:S,200PPM/250STEL; 93  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 17%  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:PETROLEUM DISTILLATES (NAPHTHA OR RUBBER SOLVENT)  
CAS:8002-05-9  
RTECS #:SE7449000  
Fraction by Wt: 3%  
OSHA PEL:400 PPM  
ACGIH TLV:400 PPM; 8990

Ingred Name:ALIPHATIC KETONE  
Fraction by Wt: 11%  
ACGIH TLV:50 PPM, MFR

Ingred Name:ALIPHATIC ESTER

Fraction by Wt: 5%  
ACGIH TLV:150 PPM, MFR

===== Hazards Identification =====

Effects of Overexposure:HEADACHE,NAUSEA,IMPAIRMENT OF REACTION TIME &  
COORDINATION.

===== First Aid Measures =====

First Aid:INH:MOVE TO FRESH AIR TO IMPROVE BREATHING. SKIN:WASH W/SOAP  
& WATER. REMOVE CONTAMINATED CLOTHING & WASH BEFORE REUSE.  
EYES:FLUSH W/WATER AT LEAST 15 MINS, CALL MD.

===== Fire Fighting Measu

res =====

Flash Point:20-73F CC

Lower Limits:1.3

Upper Limits:36.5

Extinguishing Media:FOAM, CO\*2, DRY CHEMICAL

Fire Fighting Procedures:H\*2O FOG NOZZLE:USE TO COOL CLSD CNTNR,PRVNT  
PRESS BUILD-UP.

===== Accidental Release Measures =====

Spill Release Procedures:AVOID PROLONGED CONTACT W/SKIN & BREATHING OF  
VAPOR. REMOVE SOURCES OF IGNITION. REMOVE W/INERT ABSORBENT.  
VENTILATE AREA.

===== Handling and Storage =====

=====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS, OPEN  
FLAME. CLOSE CONTAINER AFTER EACH USE. DO NOT STORE ABOVE 120F,49C.

Other Precautions:WASH THOROUGHLY AFTER HANDLING & BEFORE EATING OR  
SMOKING. OBSERVE LABEL PRECAUTIONS. CONTAINERS SHOULD BE GROUNDED  
WHEN POURING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPRVD IF AIR CONTAMINANT CONTROLK IS  
NOT FEASIBLE.

Ventilation:LOC & MECH ADEQU  
ATE TO KEEP BELOW TLV/LEL.REMOVE IGN  
SOURCES

Protective Gloves:PRLNGD/RPTD CNT

Eye Protection:SAFETY EYEWEAR

Other Protective Equipment:USE APPROPRIATE INDUSTRIAL HYGIENE  
PRACTICES.

Supplemental Safety and Health

ADDTNL INGRED:ALIPHATIC ALCOHOL,6%,TLV=400 PPM,MFR. BP:54-142C. FL  
PT:-6.7-23C CC. BP IS APPROX RANGE. VAP PRESS & VAP DENSITY ARE  
FOR PRINCIPAL SOLVENT. % OF INGREDIENTS IS APPROX.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P

. Text:129-287F

Vapor Pres:22

Vapor Density:3.10

Spec Gravity:1.174

Evaporation Rate & Reference: