

PRATT & LAMBERT, INC. -- EX-2893-66 PRIMER CTG CN ALKYD CI FD 727002 -- 8010-00-468-4205
===== Product Identification =====

Product ID:EX-2893-66 PRIMER CTG CN ALKYD CI FD 727002

MSDS Date:03/31/1986

FSC:8010

NIIN:00-468-4205

MSDS Number: BDZNV

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Preparer's Name:W

.A. ELLISON

CAGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:ZINC DICHROMATE (VI)

CAS:14018-95-2

RTECS #:HX7755000

OSHA PEL:C, 0.1 MG/M3 (CRO3)

ACGIH TLV:0.05 MG/M3 (CR);8990

Ingred Name:ALUMINUM SILICATE (AS NUISANCE

DUST OR PARTICULATES NOT
OTHERWISE REGULATED)

CAS:1302-76-7

RTECS #:BD1450000

OSHA PEL:15 MG/M3 TOTAL DUST

ACGIH TLV:10 MG/M3 TDUST;8990

Ingred Name:VM&P NAPHTHA

CAS:8030-30-6

RTECS #:ZB1601000

OSHA PEL:500 PPM

ACGIH TLV:300 PPM

Ingred Name:ISOBUTYL ALCOHOL (SARA III)

CAS:78-83-1

RTECS #:NP9625000

OSHA PEL:100 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ISOBUTYL ACETATE

CAS:110-19-0

RTECS #:NP9100000

OSHA PEL:150 PPM

ACGIH TLV:150 PPM

EPA Rpt Qty:5000

LBS

DOT Rpt Qty:5000 LBS

Ingred Name:N-HEPTANE

CAS:142-82-5

RTECS #:MI7875000

OSHA PEL:500 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9293

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:NITROCELLULOSE

CAS:9004-70-0

RTECS #:QW0970000

OSHA PEL:N/E

ACGIH TLV:N/E

Ingred Name:METHYL ETHYL KETONE

CAS:78-93-3

RTECS #:PM7780000

OSHA PEL:200 PPM

ACGIH TLV:200 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:UNKNOWN IARC:YES
Health Hazards Acute and Chronic:OVEREXPOSURE TO SOLVENTS MAY CAUSE
DAMAGE TO BRAIN AND NERVOUS SYSTEM. REPEATED AND PROLONGED
OVEREXPOSURE TO INSOLUBLE CHROMATES MAY CAUSE LUNG CANCER.
Explanation of Carcinogenicity:ZINC CHROMATE HAS BEEN LISTED AS A
POTENTIAL CARCINOGEN BY IARC
Effects of Overexposure:MAY CAUSE G
ASTROINTESTINAL IRRITATION, NAUSEA,
VOMITING AND ABDOMIAL PAIN. ANESTHETIC, MAY CAUSE HEADACHE,
DIZZINESS, EYE IRRITATION AND SKIN IRRITATION.

=====
First Aid Measures
=====

First Aid:IF SWALLOWED INDUCE VOMITING BY GIVING TWO GLASSES OF WATER
AND CONSULT PHYSICIAN OR POISON CONTROL CENTER. INHAL-REMOVE TO
FRESH AIR, KEEP WARM AND QUIET. EYE-FLUSH WITH LARGE AMOUNTS OF
WATER FOR 15 MINUTES. SKIN-WASH AFFECTED AREA WITH SOAP AND WATER.
GET MEDICAL ATTENTION FOR FIRST AID/EMERGENCY TREATMENT.

=====
Fire Fighting Measures
=====

Flash Point:20F / -7C
Extinguishing Media:CLASS B FIRE EXTINGUISHERS. POLYMER FOAM IS
PREFERRED FOR LARGE FIRES.
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS. WATE
MAY BE USED TO COOL CONTAINERS TO PREVENT PRESSURE BUILD-UP WHEN
EXPOSED TO EXTREME HEAT.
Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED ISOLATE
FROM HEAT
CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME
HEAT.

=====
Accidental Release Measures
=====

Spill Release Procedures:KEEP SPECTATORS AWAY ELIMINATE ALL IGNITION
SOURCES DIKE AND CONTAIN SPILL WITH INERT MATERIAL PUT LIQUIDS IN
COVERED METAL CONTAINERS FOR RECOVERY OR DISPOSAL PREVENT
CONTAMINATION OF SEWERS, STREAMS AND GROUNDWATER WITH SPILLED
MATERIAL

=====
Handling and Storage
=====

Handling and St

Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106

Other Precautions:DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER USE. EMPTY CONTAINERS MUST NOT BE WASHED OR RE-USED. DO NOT WELD, BRAZE OR CUT EMPTY CONTAINER. NEVER USE PRESSURE TO EMPTY.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE APPROVED NIOSH FILTER RESPIRATOR/AIR SUPPLIED RESPIRATOR.

Ventilation:PROVIDE GENERAL DILUTION AND LOCAL EXHAUST VENTILATION TO KEEP CONCENTRATION OF HAZ INGREDIENTS BELOW FLAMMABLE LIMITS.

Protective Gloves:SOLVENT IMPERMEABLE

Eye Protection:SAFETY GLASSES W/SHIELD

Other Protective Equipment:EYEWASH FACILITY, SAFETY SHOWER

Supplemental Safety and Health

CHEMICAL SPLASH GOGGLES AND/OR FACESHIELDS MAY BE REQUIRED FOR SPECIFIC APPLICATIONS.

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:175F - 475F

Vapor Density:>AIR

Evaporation Rate &

; Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:72

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS. OXIDIZING MATERIALS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION.

Hazardous Decomposition Products:BURNING WILL PRODUCE SMOKE, CARBON MONOXIDE AND CARBON DIOXIDE. OXIDES OF NITROGEN & OXIDES OF CHROMIUM MAYBE GENERATED

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL STATE AND LOCAL LAWS INCINERATE ONLY IN EPA PERMITTED FACILITY DO NOT INCINERATE CLOSED CONTAINER OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMMABLE MATERIALS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied,

warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.