

CHARTER CHEMS./CHARTER INTERN.OIL(CHEM.COMMOD.DIST -- N-HEPTANE -- 6810-00-470-4631

===== Product Identification =====

Product ID:N-HEPTANE

MSDS Date:01/01/1985

FSC:6810

NIIN:00-470-4631

MSDS Number: BDZPV

=== Responsible Party ===

Company Name:CHARTER CHEMS./CHARTER INTERN.OIL(CHEM.COMMOD.DIST

Address:8938 MANCHESTER ST

Box:5008

City:HOUSTON

State:TX

ZIP:77012-2149

Country:US

Emergency Phone Num:

NONE

CAGE:LO420

=== Contractor Identification ===

Company Name:CHARTER CHEMS./CHARTER INTERN.OIL(CHEM.COMMOD.DIST

Address:8938 MANCHESTER ST

Box:5008

City:HOUSTON

State:TX

ZIP:77012-2149

Country:US

CAGE:LO420

Company Name:CHARTER INTERNATIONAL OIL CO

Address:8938 MANCHESTER ST

Box:5008

City:HOUSTON

State:TX

ZIP:77012-2149

Country:US

CAGE:60776

===== Composition/Information on Ingredients =====

Ingred Name:N-HEPTANE

CAS:142-82-5

RTECS #:MI7700000

Fraction by Wt: 100%

OSHA PEL:

500 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9293

===== Hazards Identification =====

Effects of Overexposure:OVEREXPOSURE TO VAPORS MIGHT AFFECT CENTRAL NERVOUS SYSTEM & CAUSE RESPIRATORY IRRITATION.

===== First Aid Measures =====

First Aid:SKIN: WASH W/SOAP & WATER, AN EMOLLIENT CREAM OR LOTION IS BENEFICIAL; EYES:WASH W/PLENTRY OF WATER FOR 5 MINUTES; INHALATION: PROVIDE FRESH AIR & REST; USE ARTIFICIAL RESPIRATION IF NEEDED; INGESTION: DO NOT INDUCE VOMITING. CALL A PHYSICIAN

===== Fire Fighting Measures =====

Flash Point:25 F /-3.9C ,TCC
Lower Limits:1.0
Upper Limits:6.8
Extinguishing Media:MECHANICAL FOAM, DRY CHEMICAL, WATER FOG, CARBON DIOXIDE
Fire Fighting Procedures:A STRAIGHT WATER STREAM WOULD SPREAD OIL FIRES
Unusual Fire/Explosion Hazard:VAPOR ACCUMULATION WOULD FLASH AND/OR EXPLODE IF IGNITED

===== Accidental Release Measures =====

Spill Release Procedures:AVOID OPEN FLAME & OTHER POSSIBLE IGNITION SOURCES; PROVIDE ADEQUATE VENTILATION; COLLECT MATERIAL WITH APPROPRIATE ABSORBENT & PLACE IN APPROVED CONTAINER. DO NOT FLUSH TO SEWER OR CLOSED DRAINS.

===== Handling and Storage =====

Handling and Storage Precautions:HANDLE AS A VERY FLAMMABLE LIQUID
Other Precautions:USE PRECAUTIONS AS FOR GASOLINE

===== Exposure Controls/Personal Protection ===

=====

Respiratory Protection:SELF-CONTAINED BREATHING APPARATUS IN
INADEQUATELY VENTILATED AREA.
Ventilation:AS REQUIRED TO MAINTAIN AIR QUALITY(INGRED.CONC.)BELOW TLV
Protective Gloves:RECOMMENDED
Eye Protection:SAFETY GLASSES/GOGGLES
Other Protective Equipment:AS REQUIRED TO AVOID CONTACT WITH CLOTHING &
SKIN
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:B.P. Text:205-211 F
Vapor Pres:32
Vapor Density:3.45
Spec Gravity:0.698
Evaporation Rate & Reference:(BU-AC =1) : 4.2
Solubility in Water:NEGLIGIBLE
Appearance and Odor:WATER WHITE LIQUID; MILD ALIPHATIC HYDROCRBN ODOR
Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID STRONG OXIDIZING AGENTS, CORROSIVES
Stability Condition to Avoid:SOURCES OF IGNITION
Hazardous Decomposition Products:CARBON MONOXIDE & CARBON DIOXIDE

===== Disposal
Considerations =====

Waste Disposal Methods:DISPOSE BY INCINERATION IAW APPROPRIATE FEDERAL,
STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document

should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.