

BOSTIK-FINCH, INC. SUBSIDIARY OF USM CORPATION -- BOSTIK,FLAT:663-18 BASE,X-363 CURING SOL -- 8010-00-482-4440

=====
===== Product Identification =====

Product ID:BOSTIK,FLAT:663-18 BASE,X-363 CURING SOL

MSDS Date:01/01/1987

FSC:8010

NIIN:00-482-4440

MSDS Number: BDZXY

=== Responsible Party ===

Company Name:BOSTIK-FINCH, INC. SUBSIDIARY OF USM CORPATION

Address:434 W. MEAT ST.

City:ORANGE

State:CA

ZIP:9

2661

Country:US

CAGE:KO195

=== Contractor Identification ===

Company Name:AKZO COATINGS INC

Address:434 W. MEATS STREET

Box:City:ORANGE

State:CA

ZIP:92661

Country:US

Phone:714-637-1750; CHEMTREC 800-424-9300

CAGE:98502

Company Name:BOSTIK-FINCH, INC.

Address:434 W. MEAT ST.

Box:City:ORANGE

State:CA

ZIP:92661

Country:US

CAGE:KO195

=====
===== Composition/Information on Ingredients =====

Ingred Name:POLYESTER RESIN

Fraction by Wt: 19.1%

Ingred Name:ALIPHATIC ISOCYANATE PREPOLYMER

Fr

action by Wt: 16.5%

Ingred Name: SOLVENTS-TOLUENE, XYLENE, MEK, ETHYL ACETATE, ETYLENE GLYCOL
MONOETHYL ETHER ACETATE.

Fraction by Wt: 45.0%

ACGIH TLV: S, 100 PPM-XYLNE

Ingred Name: COLOR PIGMENTS

Fraction by Wt: 19.2%

=====
Hazards Identification
=====

Effects of Overexposure: VAPOR- IRRIT NOSE & THROAT. MAY CAUSE NAUSEA &
VOMITNG. CONTACT W/SKIN OR EYES MAY BE IRRITATNG.

=====
First Aid Measures
=====

First Aid: SKIN:

WASH AFFECTED AREA W/SOAP & WATER. EYE: IMMEDIATELY
FLUSH W/WATER FOR AT LST 15 MIN, CALL MD. INHAL: REMOVE VICTIM TO
FRESH AIR. CALL MD. INGEST: INDUCE VOMITING. CALL MD.

=====
Fire Fighting Measures
=====

Flash Point: 23F TCC

Lower Limits: 1.1

Extinguishing Media: SMALL FIRES-CO*2 OR DRY CHEM. LGE
FIRES-ALCOHOL-TYPE FOAMS.

Fire Fighting Procedures: AIR-SUPP RESCUE EQUIP. COOL CNTNRS W/WATER
SPRAY.

Unusual Fire/Explosion Hazard: DO NOT APPLY TO HE
ATED SURFS OR WHERE

ELEC SPARKS PRESNT. FIRES-H*2O INEFF EXCPT SPRAY TO ABSRB HEAT

=====
Accidental Release Measures
=====

Spill Release Procedures: ABSORB MATERIAL W/SAWDUST OR OIL-ABSORBING
COMPOUND. WASH AREA W/WATER. USE ADEQUATE VENTILATION TO CLEAR
FUMES FROM AREA. AVOID SPARKS.

=====
Handling and Storage
=====

Handling and Storage Precautions: STORE UNDER 100F. KEEP AWAY FROM HEAT,
SPARKS AND OPEN FLAME. KEEP

CONTAINERS CLOSED WHEN NOT IN USE.

Other Precautions:DO NOT STORE OR MIX WITH STRONG OXIDANTS. TO MEET TLV ASSMNG APPLCTN RATE OF 10 GAL/HR FRESH AIR REQ WILL BE 18,000-20,000 CFM, TO MEET 25% OF LEL 700-800 CFM UNDER SAME CONDITNS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:AIR-SUPP RESP OR CHEM CARTRIDGE/DUST FILTER TYPE RESP

Ventilation:ADEQUATE VENTILATION TO KEEP BELOW LWL & TLV

Protective Gloves:SOLVNT RESISTNT

Eye Protecti

on:GOGGLES OR FACE SHIELD

Other Protective Equipment:COVERALLS, APRON, NON-SPARKING SAFETY SHOES, ETC.

Supplemental Safety and Health

PRODUCT ALSO CONTAINS 0.2% SUSPENSION AND FLOW CONTROL ADDITIVES. VAPOR DENSITY: HEAVIER THAN AIR. WEIGHT/GALLON: 9.6 LBS (MIXED). MFG SUGGESTS TLV OF 100 PPM.

=====
===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:175 TO 320F

Vapor Pres:70

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles

by Volume:57.4

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDANTS

Stability Condition to Avoid:STORAGE AT HIGH TEMPERATURES.

Hazardous Decomposition Products:CO & COMBUSTION PRODS OF VARIOUS PIGMENTS EMPLOYED.

=====
===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE WITH CARE. SANITARY LANDFILL PREFERRED. (MFG REC)

Disclaimer (provided with this information by th

e compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.