

DEFT, INC -- DEFTHANE -- 8010-00-482-5648

===== Product Identification =====

Product ID:DEFTHANE  
MSDS Date:01/01/1985  
FSC:8010  
NIIN:00-482-5648  
MSDS Number: BDZYC  
=== Responsible Party ===  
Company Name:DEFT, INC  
Address:17451 VON KARMAN AVE  
City:IRVINE  
State:CA  
ZIP:92714-6205  
Country:US  
Info Phone Num:714-474-0400 / FAX 714-474-7269  
Emergency Phone Num:714-474-0400  
CAGE:5M511  
=== Contractor Identification ===  
Company Name:DEFT, INC.  
Address:17451 VON KARMAN AVE  
City:IRVINE  
State:CA  
ZIP:92614  
Country:US  
Phone:949-474-0400  
CAGE:33461  
Company Name:DEFT, INC  
Address:17451 VON KARMAN AVE  
City:IRVINE  
State:CA  
ZIP:92714-6205  
Country:US  
Phone:714-474-0400  
CAGE:5M511

===== Composition/Information on Ingredients =====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)  
CAS:1330-20-7  
RTECS #:ZE2100000  
OSHA PEL:100 PPM/150 STEL  
ACGIH TLV:100 PPM/150STEL;9192  
EPA Rpt Qty:1000 LBS  
D

OT Rpt Qty:1000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL ACETATE (SARA III)

CAS:141-78-6

RTECS #:AH5425000

OSHA PEL:400 PPM

ACGIH TLV:400 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS:111-15-9

RTECS #:KK8225000

OSHA PEL:S,100 PPM

ACGIH TLV:S, 5 PPM;

9192

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

==== Hazards Identification =====

Effects of Overexposure:EYE,THROAT,SKIN,LUNG IRRITANT,NARCOSIS

==== First Aid Measures =====

First Aid:WASH SKIN THOROUGHLY FLUSH EYES WITH WATER,REMOVE TO FRESH AIR,REMOVE CONTAMINATED CLOTHING GIVE ARTIFICIAL RESPIRATION I

F

NEEDED,CALL DOCTOR

=====  
Fire Fighting Measures  
=====

Flash Point:28F,-2.2C TOC

Extinguishing Media:FOAM,DRY CHEMICAL,CARBON DIOXIDE

Unusual Fire/Explosion Hazard:AVOID FIRE,HEAT,SPARKS,IGNITION  
SOURCES,STORAGE IN DIRECT SUNLIGHT

=====  
Accidental Release Measures  
=====

Spill Release Procedures:VENTILATE AREA MECHANICALLY,KEEP FROM  
FLAME,FIRE,SPARKS,IGNITION SOURCES;DO NOT BREATHE VAPORS;CLEAN UP  
WITH ABSORBENT MA  
TERIAL

=====  
Handling and Storage  
=====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED,UPRIGHT,AWAY  
FROM FIRE,FLAME,SPARKS,IGNITION SOURCES,DIRECT SUNLIGHT

Other Precautions:AVOID PROLONGED BREATHING OF VAPORS

=====  
Exposure Controls/Personal Protection  
=====

Ventilation:LOCAL EXHAUST

Protective Gloves:GLOVES

Eye Protection:GOGGLES/GLASSES

Supplemental Safety and Health  
KIT(2 PART SYSTEM)

=====  
Physical/Chemical  
Properties  
=====

HCC:F2

Boiling Pt:B.P. Text:175F;79.4C

Vapor Pres:18

Solubility in Water:NEGLIGIBLE

Appearance and Odor:FLAT,GREEN PAINT,PUNGENT ODOR

Percent Volatiles by Volume:59.1

=====  
Stability and Reactivity Data  
=====

Stability Indicator/Materials to Avoid:YES

=====  
Disposal Considerations  
=====

Waste Disposal Methods:SANITARY LANDFILL,KEEP IN CLOSED CONTAINERS

Disclaimer (provided with this information by th

e compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.