

AMERON INDUSTRIAL COATINGS DIVISION -- GREEN 14187 -- 8010-00-515-1567

=====
Product Identification
=====

Product ID:GREEN 14187

MSDS Date:01/01/1985

FSC:8010

NIIN:00-515-1567

MSDS Number: BFCBC

=== Responsible Party ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Address:201 N BERRY ST

City:BREA

State:CA

ZIP:92621-3904

Country:US

Info Phone Num:714-529-4597

Emergency Phone Num:714-529-4597

CAGE:09869

=== Contractor Identification ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Address:201 N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904

Country:US

Phone:714-529-4597

CAGE:09869

=====
Composition/Information on Ingredients
=====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 3.9%

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:ISOBUTYL ALCOHOL (SARA III)

CAS:78-83-1

RTECS #:NP9625000

Fraction by

Wt: 8.2%
OSHA PEL:100 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)
CAS:8030-30-6
RTECS #:SE7555000
Fraction by Wt: 19.5%
OSHA PEL:100 PPM

Ingred Name:ISOBUTYL ACETATE (SARA III)
CAS:110-19-0
RTECS #:AI4025000
Fraction by Wt: 27.0%
OSHA PEL:150 PPM
ACGIH TLV:150 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR
1910.1025),(CRO3 CEILING 0.1 MG/M3)
CAS:7758-97
-6
RTECS #:GB2975000
Fraction by Wt: 10.7%
OSHA PEL:0.05 MG/M3 (PB)
ACGIH TLV:0.05MG/M3(CR)A2;8990

=====
===== Hazards Identification =====

Effects of Overexposure:ANESTHETIC, IRR. OF RESPIRATORY TRACT OR ACUTE
NERVOUS SYS. DEPRESSION, EYE & SKIN IRRITATION

=====
===== First Aid Measures =====

First Aid:IN CASE OF CONTACT FLUSH SKIN AND EYES WITH WATER AND REMOVE
CONTAMINATED CLOTHING. IF INHALED REMOVE TO FRESH AIR. CAL A

PHYSICIAN IF CONDITIONS PERSIST.

===== Fire Fighting Measures =====

Flash Point:30F

Lower Limits:0.9

Extinguishing Media:SMALL FIRES-CARBON DIOXIDE OR DRY CHEM. LARGE FIRES-FOAM

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS FOR FIREMEN

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION.

AVOID

BREATHING VAPORS. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE FLAMMABLES.

Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN DURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES

===== Exposure Controls/Personal Protection =====

Respira

tory Protection:USE NIOSH APPROVED PAINT RESPIRATOR OR AIR SUPPLIED RESPIRATOR

Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST AS NECESSARY

Supplemental Safety and Health

DA0700000 ETHYL BENZENE 1.3 PER CENT RESPIRATOR USE BASED ON CHEM. CONC. AND CONDITIONS OF USE.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:118-321F

Vapor Density:>1

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:74.5

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

Stability Condition to Avoid: AVOID FIRE, HEAT AND HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.