View NSN Online: https://aerobasegroup.com/nsn/8010-00-515-1567

PRATT & LAMBERT-WICHITA DIV -- 786430 LACQUER C/N CLOSS LIGHT GREEN 14187 - 8010-00-515-1567

Product ID:786430 LACQUER C/N CLOSS LIGHT GREEN 14187 MSDS Date:01/01/1985 FSC:8010 NIIN:00-515-1567 **MSDS Number: BFCBD** === Responsible Party === Company Name: PRATT & LAMBERT-WICHITA DIV Address:16116 E 13TH ST Box:2153 City:WICHITA State:KS ZIP:67201 Country:US CAGE:KO 010 === Contractor Identification === Company Name: PRATT & LAMBERT-WICHITA DIV. Box:2153 CAGE:KO010 Company Name: PRATT AND LAMBERT INC Address:Box:6027 City:CLEVELAND State:OH ZIP:44101-1027 Country:US Phone:216-566-2902 CAGE:61196 Ingred Name:LIGHT CHROME GREEN LD 50 VALUE>10.000 GMS/KG

Fraction by Wt: 8%

Ingred Name:ISOBUTYL ACETATE RTECS #:NP9100000 Fraction by Wt: 15% ACGIH TLV:150 PPM

Ingred Name: ISOBUTYL ALCOHOL (SAR

A III) CAS:78-83-1 RTECS #:NP9625000 Fraction by Wt: 15% OSHA PEL:100 PPM ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS
Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN) CAS:8030-30-6 RTECS #:SE7555000 Fraction by Wt: 15% OSHA PEL:100 PPM
Ingred Name:LEAD CHROMATE PIGMENT LD 50 VALUE >10.000 GMS/KG
======================================
Effects of Overexposure:INHAL:ANEST,IRRIT OF RESPIR TRACT OR ACUT NERV SYS DEPRESN,HDACH,DIZZ,CONFUS,UNC ONSCIOUS, COMA.
======================================
First Aid:IN CASE OF CONTACT, FLUSH SKIN & EYES W/PLENTY OF WATER WHILEREMOVING CONTAMINATED CLOTHING. IF INHALED, REMOV TO FREAH AIR. CALL A PHYSICIAN IF SYMPTOMS PERSIST.
======================================
Flash Point:50 F TCC 10 C Lower Limits:.90 Extinguishing Media:USE FIRE EXTING(CO*2,DRY CHEM OR ALCOH FOAM)LO
FIRE-POLYMER Fire Fighting Procedures:SELF-CONTAI
NED BREATH APPARATUS SHLD BE AVAIL F/FIREMEN.
Unusual Fire/Explosion Hazard:KEEP CONTNRS TIGHTLY CLOS:ISOLAT FR HEAT,ELECTR EQPMT,SPARKS & OPEN FLAME.CLOS CONTNRS MAY EXPLO(SUP
======================================
Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES,HOT SURFACES,& ELECTRICAL, STATIC, OR FRICTIONAL SPARKS) AVOID BREATHING VAPORS.VENTILATE AREA. REMOVE W/INERT ABSORBENT &

=================== Ha

NON-SPARKING TOOLS.

Handling and Storage Precautions:DO NOT STORE ABOVE 120 F. STORE LG QUANTITIES IN BLDG DESIGNED TO COMPLY W/OSHA 1910.106
Other Precautions:CONTNRS GROUNDED WHEN POURING.AVD FRE FAL OF LIQD IN EXCES OF FEW INCHES.DON'T FLAM CUT,BRAZE OR WELD COATED MATERIALW/O BUR OF MNES APRVD RESPIRATR OR APPROPVENT.AD LABL WARN"DO NOT TAK INTER

Respiratory Protection:OUTDOOR/OPEN A REAS,USE BUR. OF MINES APPRVD MECH FILTER RESPIRATOR. Ventilation:PROVID GEN DILUT OR LOC EXHAUSTVENT IN VOL TO KP BELOW TLV. Protective Gloves:F/REPTD CONTACT Eye Protection:SAFETY EYEWEAR. Other Protective Equipment:PRVNT PROLNG SKIN CONTACT TO CONTAMINATED CLOTHING. Supplemental Safety and Health UNUS FIRE & EXPLOS HAZ:WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY TO

VERY HOT SURFACES.

HCC:F3 Boiling Pt:B.P. Text: 175-290 F Vapor Density:HEAV Evaporation Rate & amp; Reference:SLOWER THAN ETHER Percent Volatiles by Volume:75

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:AVOID FIRES,HEAT & HOT SURFACES

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOC,STATE & FEDERAL REGULATIONS.INCINERATE IN APPRVD FACILITY.DO NOT INCINERATE CLOSED CON

TAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particul

ar situation.