

GATES ENGINEERING CO.,INC -- GACO N-700-A GREY -- 8030-00-515-2488

=====  
Product Identification  
=====

Product ID:GACO N-700-A GREY

MSDS Date:01/01/1985

FSC:8030

NIIN:00-515-2488

MSDS Number: BFCFK

=== Responsible Party ===

Company Name:GATES ENGINEERING CO.,INC

Address:100 S. WEST STREET

City:WILMINGTON

State:DE

ZIP:19801

Country:US

Info Phone Num:302-656-9951

Emergency Phone Num:302-656-9951

CAG

E:88112

=== Contractor Identification ===

Company Name:GATES ENGINEERING CO.,INC.

Address:100 S. WEST STREET

Box:City:WILMINGTON

State:DE

ZIP:19801

Country:US

Phone:.....DISCONNECTED....

CAGE:88112

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE21

00000  
OSHA PEL:100 PPM/150 STEL  
ACGIH TLV:100 PPM/150STEL;9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:PETROLEUM SOLVENTS

Ingred Name:PIGMENTS  
Fraction by Wt: 16%

Ingred Name:VEHICLE (TYPE NOT SPECIFIED)  
Fraction by Wt: 21%

=====  
Hazards Identification  
=====

Effects of Overexposure:SKIN/EYE CONT:BRIM IRRIT.INHALATION:IRRIT OF  
RESP TRACT,HEADACHE,DIZZINESS,UNCONSCIOUSNESS.

=====  
First Aid Measures  
=====

=

First Aid:INHAL:REMOVE TO FRESH AIR,RESTORE BREATH,NOTIFY MD.EYE:FLUSH  
W/WATER 15 MIN,TAKE TO DR.SKIN:WASH W/WATER,REMOVE CONTAMINATED  
CLOTHING,CONSULT DR.

=====  
Fire Fighting Measures  
=====

Flash Point:.40F/4C ASTM D  
Lower Limits:0.9  
Upper Limits:7  
Extinguishing Media:DRY CHEMICAL,CARBON DIOXIDE,FOAM  
Fire Fighting Procedures:SELF-CONT BREATH APPART,PROTECTIVE CLOTHING.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:ABSORB AND DISPOSE OF IN ACCORDANCE WITH LOCAL  
REGS.REMOVE ALL SOURCES OF IGNITION AND VENTILATE AREA

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN COOL,DRY PLACE.USE ONLY WITH  
ADEQUATE VENTILATION.AVOID FLAMES,SPARKS,HOT SURFACES AND STRONG  
OXIDIZERS

Other Precautions:AVOID CONTACT WITH EYES AND SKIN.DO NOT TAKE  
INTERNALLY.EXHAUST SOLVENT VAPORS WHICH COLLECT NEAR FLOORS.

=====  
Exposure Co

ntrols/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH  
EXPOSURE OF CONCERN

Ventilation:LOCAL EXHAUST

Protective Gloves:RECOMMENDED

Eye Protection:RECOMMENDED

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Vapor Density:>1

Spec Gravity:1

Evaporation Rate & Reference: