

PRATT & LAMBERT, INC.-INDUSTRIAL COATINGS DIV. -- ENAMEL, ALKYD,LUSTERLESS 741402 --
8010-00-526-1610

=====
===== Product Identification =====

Product ID:ENAMEL, ALKYD,LUSTERLESS 741402

MSDS Date:03/11/1988

FSC:8010

NIIN:00-526-1610

MSDS Number: BFCMQ

==== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.-INDUSTRIAL COATINGS DIV.

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Co

Country:US

Preparer's Name:W. A. ELLISON

CAGE:FO127

==== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====
===== Composition/Information on Ingredients =====

Ingred Name:VM&P NAPHTHA (LIGROINE)

CAS:8032-32-4

RTECS #:OI6180000

OSHA PEL:300 PPM/400 STEL

ACGIH TLV:300 PPM; 9192

Ingred Name:MINERAL SPIR

ITS
CAS:64475-85-0
RTECS #:PY8240000
OSHA PEL:500 PPM
ACGIH TLV:100 PPM

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3; 9192

Ingred Name:LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR
1910.1025),(CRO3 CEILING 0.1 MG/M3)
CAS:7758-97-6
RTECS #:GB2975000
OSHA PEL:0.05 MG/M3 (PB)
ACGIH TLV:0.05MG/M3(CR)A2;8990

Ingred Name:SILICA, CRYSTALLINE - CRISTOBALITE
CAS:14464-46-1
RTECS #:VV7325000
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.05 MG/M3 RDUST9293

Ingre
d Name:SILICA, CRYSTALLINE - FUSED
CAS:60676-86-0
RTECS #:VV7328000
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:TALC (CONTAINING NO ASBESTOS)
CAS:14807-96-6
RTECS #:WW2710000
OSHA PEL:2 MG/M3 RDUST
ACGIH TLV:2 MG/M3 RDUST; 9192

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES
Health Hazards Acute and Chronic:REPEATED EXPOSURE TO CRYSTALLINE
SILIC

A MAY CAUSE PNEUMOCONIOSIS, A PROGRESSIVELY DISABLING LUNG DISEASE; RELATIVELY INSOLUBLE CHROMATES MAY CAUSE LUNG CANCER; CHRONIC OVEREXPOSURE TO LEAD MAY RESULT IN DAMAGE TO BLOOD FORMING, NERVOUS, URINARY & REPRO SYSTEM; SOLVENT HAVE BEEN ASSOCIATED WITH PERM BRAIN & NERVOUS SYS DAMAGE

Explanation of Carcinogenicity: CHROM & CERTAIN CHROM COMP ARE LISTED AS POTENTIAL CARCIN BY NTP & IARC. LEAD CHROM POTENTIAL ANIMAL CARCIN BY IARC.

Effects of Overexposure: SWALLOWING-GASTROINTESTINAL IRRITATION, NAUSEA

& VOMITING. ASPIRATION OF MATERIAL INTO LUNG MAY CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. INHALED-MAY CAUSE NOSE & THROAT IRRITATION. HIGH CONCENTRATIONS MAY CAUSE ACUTE NERVOUS SYSTEM DEPRESS. EYE-MAY CAUSE EYE IRRITATION. SKIN-MAY CAUSE DEFATTING AND IRRITATION OF SKIN

Medical Cond Aggravated by Exposure: PRE-EXISTING KIDNEY CONDITION MAY BE AGGRAVATED BY EXPOSURES TO LEAD; PRE-EXISTING RESPIRATORY CONDITION MAY BE AGGRAVATED BY EXPOSURE TO CRYSTALLINE SILICA.

=====
===== First Aid Measures =====

First Aid: IF SWALLOWED-DO NOT INDUCE VOMITING. CALL POISON CONTROL CENTER, HOSPITAL EMERG ROOM OR MD IMMEDIATELY. INHALED-REMOVE TO FRESH AIR IMMEDIATELY. IF BREATHING HAS STOPPED, GIVE ARTIFICIAL RESPIRATION. KEEP WARM & QUIET. MED ATTN IMMEDIATELY. EYE-FLUSH WITH LARGE AMOUNTS OF WATER AT LEAST 15 MIN. GET MED ATTN. SKIN-REMOVE CONTAMINATED CLOTHING. WASH AFFECTED AREA WITH SOAP & WATER. MED ATTN I

F
IRRITATION PERSISTS.

=====
===== Fire Fighting Measures =====

Flash Point: 102F-39C

Extinguishing Media: NFPA CLASS B FIRE EXTINGUISHER DESIGNED TO EXTINGUISH FLAMMABLE LIQUID FIRES. POLYMER FOAM PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS. WATER MAY BE INEFFECTIVE, BUT MAY BE USED TO PREVENT PRESSURE BUILD-UP. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE.

Unusual Fire/Explosion Hazard: OVEREXPOSURE

TO DECOMP PROD MAY CAUSE A
HEALTH HAZARD.OBTAIN MED ATTN.KEEP CONTAINER TIGHTLY CLOSED.ISOLATE
FROM HEAT, ELEC EQUIP, SPARKS & FLAME.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIM ALL IGNITION
SOURCES. DIKE & CONTN SPILL WITH INERT MATL. TR LQDS TO COV MTL
CNTNR FOR RECOV OR DISP OR REM W/INERT ABSORB. USE NON-SPRKG
TOOLS.PLACE ABSORB MAT IN COV METAL CONTNR FOR DISP.PREVENT CONTAM
OF SEW,STRMS,E

TC

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95 DEGREES F. STORE
LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106.

Other Precautions:DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH
USE. DO NO BREATHE SANDING DUST. DO NOT WASH AND RE-USE CONTAINERS
FOR ANY PURPOSE. DO NOT WELD, BRAZE OR CUT ON EMPTY CONTAINER.
NEVER USE PRESSURE TO EMPTY.

===== Exposure Controls/Personal Protection

=====

Respiratory Protection:REFER TO OSHA STD 29CFR1910.1025 FOR RESPIR
PROTECTION FOR LEAD.WELL-VENTILATED AREA,RESPIR PROTECT NOT
REQUIRED.RESTRICTED AREA,NIOSH APPROVED CHEM CART RESPIR MAY BE
REQUIRED.CONFINED AREA,NIOSH/MSH A APPROVED AIR-SUPPLIED RESPIR.

Ventilation:PROVIDE GENERAL DILUTION & LOCAL EXHAUST VENTILATION.
LEAD-REFER TO OSHA STANDARDS 29CFR1910.1025 FOR VENTILATION.

Protective Gloves:SOLVENT IMPERMEABLE GLOVES

Eye Protection:WEAR SAFETY SPECTACLES

Ot

her Protective Equipment:AS REQUIRED TO PREVENT SKIN CONTACT. SEE
OSHA STANDARD FOR LEAD

Supplemental Safety and Health

SOLVENT IMPERMEABLE GLOVES ARE REQUIRED FOR REPEATED OR PROLONGED
CONTACT.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:280F-388F

Vapor Pres:2

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:58

===== Stability and Reactivity Data =====

Stab

ility Indicator/Materials to Avoid: YES

STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid: AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION.

Hazardous Decomposition Products: BURNING, WHEN HEATED BY WELDING OR CUTTING, WILL PRODUCE SMOKE, CARBON MONOX & CARBON DIOX. MAYBE OXIDES OF LEAD.

Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT SPARKS AND FLAME.

===== Disposal Considerations =====

Waste Disposal Methods: IAW FED, STATE & LOCA

L LAWS. INCINERATE ONLY IN

EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMMABLE MATERIALS.

CONTAMINATED ABSORBANT MAY BE DISPOSED IN A HAZARDOUS WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.