

PRATT AND LAMBERT INC -- 741-402 -- 8010-00-526-1612

===== Product Identification =====

Product ID:741-402
MSDS Date:01/01/1985
FSC:8010
NIIN:00-526-1612
MSDS Number: BFCMV
=== Responsible Party ===
Company Name:PRATT AND LAMBERT INC
Address:945 BURLINGTON
City:KANSAS CITY
State:MO
ZIP:64141
Country:US
Emergency Phone Num:316-733-1361
CAGE:92216

=== Contractor Identification ===

Company Name:PRAT
T AND LAMBERT INC
Address:945 BURLINGTON
Box:206
City:KANSAS CITY
State:MO
ZIP:64141
Country:US
CAGE:92216

===== Composition/Information on Ingredients =====

Ingred Name:LEAD (SARA III)
CAS:7439-92-1
RTECS #:OF7525000
Fraction by Wt: 6.65%
OSHA PEL:0.05 MG/M3;1910.1025
ACGIH TLV:0.15 MG/M3;DUST 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)
CAS:8030-30-6
RTECS #:SE7555000
Fraction by Wt: 35.0%
OSHA PEL:100 PPM

Ingred Name:TRIETHYLA

MINE (SARA III)
CAS:121-44-8
RTECS #:YE0175000
Fraction by Wt: 0.3%
OSHA PEL:25 PPM/15 STEL
ACGIH TLV:10 PPM/15 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOBUTYL ALCOHOL (SARA III)
CAS:78-83-1
RTECS #:NP9625000
Fraction by Wt: 0.3%
OSHA PEL:100 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Effects of Overexposure:INHAL:ANESTHETIC & IRRITATION TO
AIRWAY;IRRITATION-SKIN/EYE;
HEADACHE,DIZZY COMA.

===== First Aid Measures =====

First Aid:FLUSH SKIN/EYES W/PLENTY OF WATR. REMOVE CONTAMANITED
CLOTHING.INHAL:REMOVE TO FRESH AIR. CALL DR.IF NEEDED.

===== Fire Fighting Measures =====

Flash Point:104 F, 40 C, TCC
Lower Limits:1.1
Extinguishing Media:CARBON DIOXIDE/DRY CHEM.SMALL;POLYMER FOAM-LARGE
FIRE
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS AVAILABLE
FOR FIREMEN
Unus
ual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY
EXPLODE DUE TO PRESSURE BUILD-UP.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF
IGNITION(FLAMES,SPARKS...).AVOID BREATHING VAPORS.VENTILATE
AREA.REMOVE W/INERT ABSORBENT & NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE
AMTS. IN BUILDING

S CONSTRUCTED FOR STORAGE OF NFPA CLASS ONE

FLAMMABLE (OR COMBUSTIBLE) LIQUID.

Other Precautions: DO NOT INGEST. GROUND CONTAINERS WHEN POURING. AVOID FREE FALL OF A FEW INCHES. DO NOT FLAME CUT, BRAZE, OR WELD COATED MATERIAL W/O VENTILATION.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection: APPROVED BUREAU OF MINES RESPIRATORS W/ PROPER FILTER OR HOOD

Ventilation: GENERAL DILUTION/LOCAL EXHAUST FOR TLV&LEL SAFETY & WELDING

Protective Gloves: AL

END OF USE

Eye Protection: IF SPLASHING

Other Protective Equipment: PREVENT PROLONGED SKIN CONTACT TO CONTAMINATED CLOTHING.

Supplemental Safety and Health

BOILING RANGE 155-189 C.

=====
===== Physical/Chemical Properties =====

HCC: F4

Boiling Pt: B.P. Text: 311-373 F

Evaporation Rate & Reference: < ETHER

Appearance and Odor: GREEN PAINT.

Percent Volatiles by Volume: 60.0

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to

Avoid: YES

Stability Condition to Avoid: FIRES, HEAT & HOT SURFACES

=====
===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE IAW LOCAL, STATE & FED. LAWS. INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied

, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.