

ENMAR -- BLACK 17038,ENAMEL ALKYD GLOSS 742-702 -- 8010-00-527-2053

=====  
Product Identification  
=====

Product ID:BLACK 17038,ENAMEL ALKYD GLOSS 742-702

MSDS Date:01/01/1985

FSC:8010

NIIN:00-527-2053

MSDS Number: BFCRG

=== Responsible Party ===

Company Name:ENMAR

Address:201 N BERRY ST

City:BREA

State:CA

ZIP:92621-3904

Country:US

CAGE:OO111

=== Contractor Identification ===

Company Name:AMERON IN

DUSTRIAL COATINGS DIVISION

Address:201 N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904

Country:US

Phone:714-529-4597

CAGE:09869

Company Name:ENMAR

Address:201 N BERRY ST

Box:City:BREA

Phone:(316)-7333-1361

CAGE:OO111

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

OSHA PEL:100 PPM

=====  
Hazards Identification  
=====

Effects of Overexposure:INH:ANESTHETIC, I

IRRIT OF RESP TRACT OR ACUTE  
CNS DEPRESSION W/HDACHE,DIZ,UNCON,COMA. SKIN & EYE:IRRIT.

=====  
First Aid Measures  
=====

First Aid:IN CASE OF CONTACT, FLUSH SKIN & EYES W/PLENTY OF WATER WHILE REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOVE TO FRESH AIR. CALL A PHYSICIAN IF SYMPTONS PERSIST.

=====  
Fire Fighting Measures  
=====

Flash Point:85F TCC  
Lower Limits:1.1  
Extinguishing Media:SM FIRES:CO\*2,DRY CHEM. LG FIRE  
S:POLYMER FOAM  
PREFERRED  
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS.  
Unusual Fire/Explosion Hazard:CLOSED CONTANERS EXPOSED TO HEAT MAY EXPLODE DUE TO PRESSURE BUILD-UP

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAME, HOT SURFACES, & ELECTRICAL, STATIC, OR FRICTIONAL SPARKS).AVOID BREATHING VAPORS. VENTILATE AREA.REMOVE W/INERT ABSORBENT & NON-SPARKING TOOLS.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LG QTY IN BLDG DESIGNED TO STORE NFPA CLASS ONE FLAM LIQ. DO NOT TAKE INTERNALLY.ADD LABEL WARNING.  
Other Precautions:GROUND CONTANERS WHEN POURING. AVOID FREE FALL OF LIQ. IN EXCESS OF FEW IN. DO NOT FLAME CUT, BRAZE OR WELD COATED MATERIAL W/O APPROVED RESPIRATOR OR APPROPRIATE VETILATION.  
DOT:FLAM LIQUID.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:RESTRICT VENT:CHEM-MECH FLTR.CLSE:AIR-LINE TYPE  
Ventilation:GEN DILTN/LOCAL EXHST TO KEEP TLV/LEL BELOW LIMIT, REMOVE FUME  
Protective Gloves:YES  
Eye Protection:YES, FOR SPLASH  
Other Protective Equipment:AVOID LONG EXPOSURE TO CONTAMINATED CLOTHING.  
Supplemental Safety and Health  
VAPOR PRESSURE:3.2;VAPOR DENSITY:HEAVIER THAN AIR;WT PER GALLON:7.58 LBS.

=====  
Physical/Chemical Properties  
=====

HCC:F3  
Boiling Pt:B.P

. Text:311-373F

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:64.3

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:AVOID FIRES, HEAT & SHOT SURFACES.

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE CLOSED CONTAINER. DISPOSE IN ACCORDANCE W/FED., STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.