

PRATT AND LAMBERT INC -- ENAMEL ALKYD GLOSS BLACK 17038 -- 8010-00-527-2053

=====  
Product Identification  
=====

Product ID:ENAMEL ALKYD GLOSS BLACK 17038

MSDS Date:01/01/1987

FSC:8010

NIIN:00-527-2053

MSDS Number: BFCRH

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone

Num:716-873-6000 DOT EMER 8002553924

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====  
Composition/Information on Ingredients  
=====

Ingred Name:\*MINERAL SPIRITS

CAS:64475-85-0

RTECS #:PY8240000

ACGIH TLV:100PPM

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA

Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:CARBON BLACK  
CAS:1333-86-4  
RTECS #:FF5800000  
OSHA PEL:3.5 MG/M3  
ACGIH TLV:3.5 MG/M3; 9192

=====  
Hazards Identification  
=====

Effects of Overexposure:MATRL INTO LUNGS CAN CAUS CHEM PNEUMONITIS  
WHICH CAN BE FATAL.INHAL:NAUSEA,UNCONSCIOUS,EVN ASPHYXIAT

=====  
First Aid Measures  
=====

First Aid:SWALLOWED:INDUC VOMIT IMMED.GIVNG 2 GLASSES OF WATER &  
STICKING FINGER DO  
WN THROAT.CONSULT DR OR POISON CONTROL  
CENTR.IMMED.(NVR GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS  
PERSON.)INHAL:REMOV TO FRESH A IR IMMED.IF BREATH HAS STOP,GIVE  
ARTIF RESPIRATION

=====  
Fire Fighting Measures  
=====

Flash Point:80F,27C  
Extinguishing Media:CL B FIRE EXTING(CO\*2,ALL PURPOS DRY CHEM OR ALCOH  
FOAM)  
Fire Fighting Procedures:FIREFIGHTERS SHOULD WEAR SELF-CONTND BREATHING  
APPARATUS  
Unusual Fire/Explosion Hazard:KP CONTNRS TIGHTLY CL  
OS.ISOLAT FR  
HEAT,ELECT EQPMT,SPARKS & FLAME.CLOS CONTNRS MAY EXPLOD EXPOS(SUP)

=====  
Accidental Release Measures  
=====

Spill Release Procedures:KEEP SPECTATORS AWAY.ELIM ALL IGNIT  
SOURCES(FLAMES,HOT SURFACES & SOURCES OF ELECTR,STATIC OR  
FRICTIONAL SPARKS).DIKE & CONTN SPILL W/INERT MATRL (E.G.  
SAND,EARTH).TRANSFR LIQDS TO COVERED METAL CONTN RS F/RECOVERY OR  
DISPOS,OR REMOV INERT ABSORB.

=====  
Handling and Storage  
=====

=====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LG  
QUANTITIES IN COMPLIANCE W/OSHA 29CFR1910.106.

Other Precautions:DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH  
USE.

===== Exposure Controls/Personal Protection =====

Ventilation:PROVIDE GEN DILUT & LOC EXHAUST VENTIL IN SUFFICIENT  
VOLUME.

Protective Gloves:SOLVNT IMPERMEA

Eye Protection:SAFETY SPECTACLES W/SIDE

Other Protective Equipment:NOT LIKELY TO BE NEEDED

Supplemental Safety  
and Health

\*INDICATES SOLVENT. UNUS. FIRE & EXPLOS HAZ: EXPOSED TO EXTREME HEAT.

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:244-399F

Vapor Density:HEAV

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:62

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS

Stability Condition to Avoid:NONE KNOWN

Hazardous Decompositio

n Products:BURNING,INCLD WHN HEAT BY

WELD,CUTTING,WILL PRODUC SMOK CO(S

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORD W/FED,STATE & LOC

LAWS.INCINERATE ONLY IN EPA PERMITTED FACILITY.DO NOT INCIN CLOS

CONTRNS.OBSERVE PRECAUTIONS F/DISPOS OF FLAMMBL MATRLS.CONTAMINATED

ABSORBANT MAY BE DISPOS IN A HA Z WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):

This information is formul

ated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.