

KOPPERS CO.,INC. -- LACQUER ACRYLIC MIL-L-19537C AM.3 -- 8010-00-527-2478

=====
Product Identification
=====

Product ID:LACQUER ACRYLIC MIL-L-19537C AM.3

MSDS Date:01/01/1985

FSC:8010

NIIN:00-527-2478

MSDS Number: BFCSD

=== Responsible Party ===

Company Name:KOPPERS CO.,INC.

Address:3000 KOPPERS BLDG

City:PITTSBURGH

State:PA

ZIP:15219-1818

Country:US

CAGE:LO335

=== Contractor Identification ===

C

Company Name:KOPPERS CO INC

Address:3000 KOPPERS BLDG

Box:City:PITTSBURGH

State:PA

ZIP:15219-1818

Country:US

CAGE:80592

Company Name:KOPPERS CO.,INC.

Address:3000 KOPPERS BLDG

Box:City:PITTSBURGH

State:PA

ZIP:15219-1818

Country:US

CAGE:LO335

=====
Composition/Information on Ingredients
=====

Ingred Name:ACRYLIC/NITROCELLULOSE

Fraction by Wt: 22.9%

Ingred Name:N-BUTYL ACETATE (SARA III)

CAS:123-86-4

RTECS #:AF7350000

Fraction by Wt: 15%

Other REC Limits:NONE RECOMMENDED

OSHA

PEL:150 PPM
ACGIH TLV:150 PPM/200STEL;9394
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingr Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 34%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM
ACGIH TLV:200 PPM/300STEL;9394
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingr Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 8%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingr Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 3%
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

=====
===== Hazards Identification =====

Effects of Overexposure:SYSTEMIC TOXIC EFFECTS MAY ALSO RESULT FR SKIN
ABSORPTION.IRRIT.TO EYES,NOSE & THROAT NR OR ABOVE

=====
===== First Aid Measures =====

First Aid:IF INHALED,REMOVE TO FRESH AIR.IF NOT BREATHING,GIVE
ARTIFICIAL RESPIRAT

ION,PREFER MOUTH TO MOUTH CALL A PHYS.IN CASE OF
SKIN CONTACT,WASH THOROUGHLY W/SOAP & WATER;FOR EYES,FLUSH
IMMED.W/PLENTY OF WA TER F/15 MIN & CNTCT A PHYS.WASH CONTAMNATD
CLOTHI

=====
Fire Fighting Measures
=====

Flash Point:23F TCC -5C
Extinguishing Media:FOAM,DRY CHEMICAL,WATER SPRAY FOG OR CO*2.
Fire Fighting Procedures:USE AIR SUPPLIED EQPMENT F/ENCL. AREAS.COOL
EXPOS CONTAINERS
Unusual Fire/Explosion Hazard:KEEP AWAY FROM HEAT,SPARKS & F
LAME.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF
IGNIT(FLAME,ELECTRICAL,STATIC OR FRICTIONAL SPARKS;HOT
SURFACES,ETC).AVOID BREATHING VAPORS.VENTILATE AREA.CONTAIN & SCOOP
UP SPILL W/NON-SPARKING TOOLS,RAGS,ETC.USE INERT ABSORB ENT MATRLS
ON SM SPILLS OR ON RESIDUALSO F LG SPIL

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED & UPRI
GHT TO
PREVENT LEAKAGE.AVOID BREATHING OF VAP OR SPRAY MIST.AVOID EYE &
SKIN CONTACT.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:ORGANIC VAP CANISTER WHERE OXYG CONTNT IS ADEQ &
VAP CONCENT IS LESS
Ventilation:LOC EXHAUST-YES MECH-YES
Protective Gloves:RUBBER GLOVES
Eye Protection:GOGGLES
Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:F2
Vapor Density:HEAV
Spec Gravity:8.5 GL

Evaporation Rate & Reference:N.BUTYL ACET-FAST
Appearance and Odor:GRAY VISCOUS LIQUID W/TYPICAL SOLVENT ODOR
Percent Volatiles by Volume:73

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORD W/LOCAL APPLICABLE
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.