

AMERON INDUSTRIAL COATINGS DIVISION -- GREEN #34151 -- 8010-00-527-2495

=====
Product Identification
=====

Product ID:GREEN #34151

MSDS Date:01/01/1987

FSC:8010

NIIN:00-527-2495

MSDS Number: BFCSV

=== Responsible Party ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Emergency Phone Num:316-7331361

CAGE:09869

=== Contractor Identification ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

A

Address:201 N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904

Country:US

Phone:714-529-4597

CAGE:09869

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 16.0%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 9.0%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150S

TEL:9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ISOBUTYL ALCOHOL (SARA III)
CAS:78-83-1
RTECS #:NP9625000
Fraction by Wt: LT5%
OSHA PEL:100 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOBUTYL ACETATE (SARA III)
CAS:110-19-0
RTECS #:AI4025000
Fraction by Wt: 19.0%
OSHA PEL:150 PPM
ACGIH TLV:150 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR
1910.1025),(CRO3 CEILING 0.1 MG/M3)

CAS:7758-97-6
RTECS #:GB2975000
Fraction by Wt: 3.0%
OSHA PEL:0.05 MG/M3 (PB)
ACGIH TLV:0.05MG/M3(CR)A2;8990

=====
Hazards Identification
=====

Effects of Overexposure:ANESTHETIC, IRR. OF RESPIRATORY TRACT OR ACUTE
NERVOUS SYS. DEPRESSION, EYE & SKIN IRRITATION

=====
First Aid Measures
=====

First Aid:IN CASE OF CONTACT FLUSH SKIN AND EYES WITH WATER AND REMOVE
CONTAMINATED COTHING. IF INHALED REMOVE TO FRESH AI

R. CALL A
PHYSICIAN IF CONDITIONS PERSIST.

=====
Fire Fighting Measures
=====

Flash Point:40F TCC
Lower Limits:1.0
Extinguishing Media:SMALL FIRES-CARBON DIOXIDE OR DRY CHEM. LARGE
FIRES-FOAM
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS FOR FIREMEN
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY
EXPLODE

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCE
S OF IGNITION.AVOID
BREATHING VAPORS. REMOVE WITH INERT ABSORBENT AND NON-SPARKING
TOOLS

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE
QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE
FLAMMABLES.
Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID
FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE NIOSH APPROVED PAINT RESPIRATOR OR AIR
SUPPLIED RESPIRATOR
Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST AS NECESSARY
Supplemental Safety and Health
NT8050000ISOPROPYL ALCOHOL 7.0 PER CENT.RESPIRATOR USE BASED ON CHEM.
CONC. AND CONDITIONS OF USE.

=====
Physical/Chemical Properties
=====

Boiling Pt:B.P. Text:175-287F
Vapor Density:>1
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:73

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

Stability Condition to Avoid: AVOID FIRE, HEAT AND HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements

of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.