View NSN Online: https://aerobasegroup.com/nsn/8010-00-527-2507

KOPPERS CO., INC -- LACQ-ACRYLIC MIL-L-19537C AN. 3 -- 8010-00-527-2507

Product ID:LACQ-ACRYLIC MIL-L-19537C AN. 3 MSDS Date:01/01/1985 FSC:8010 NIIN:00-527-2507 **MSDS Number: BFCTR** === Responsible Party === Company Name: KOPPERS CO., INC Address:3000 KOPPERS BLDG City:PITTSBURGH State:PA ZIP:15219-1818 Country:US CAGE:6V069 === Contractor Identification === Compa ny Name:KOPPERS CO INC Address:3000 KOPPERS BLDG Box:City:PITTSBURGH State:PA ZIP:15219-1818 Country:US CAGE:80592 Company Name: KOPPERS CO., INC. Address:950 KOPPERS BLDG. Box:City:PITTSBURGH State:PA ZIP:15219 Phone:(412) 227-2000 CAGE:6V069

Ingred Name:ACRYLIC/NITROCELLULOSE Fraction by Wt: 26.3%

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III) CAS:78-93-3 RTECS #:EL6475000 Fraction by Wt: 29.0% Other REC Lim

its:NONE RECOMMENDED
OSHA PEL:200 PPM
ACGIH TLV:200 PPM/300STEL;9394
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (HEXONE) (SARA III) CAS:108-10-1 RTECS #:SA9275000 Fraction by Wt: 3.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:100 PPM ACGIH TLV:50 PPM/75 STEL; 9394 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:N. PROPYL ACETATE RTECS #:UN7700000 Fraction by Wt: 18.2% ACGIH TLV:200PPM

Effects of Overexposure:SYSTEMIC TOXIC EFFECTS MAY ALSO RESULT FR SKIN ABSORB.IRRIT TO EYES,NOSE & THROAT NR OR ABOV 50 PPM

First Aid:IF INHALED, REMOV TO FRESH AIR.IF NOT BREATHING, GIVE ARTIF RESPIRATION, PREFERAB MOUTH TO MOUTH.CALL A DR.IN CASE OF SKIN CON

TACT, WASH THOROUGHLY W/SOAP & WATER; FOR EYES, FLUSH IMMED.W/PLENTY OF WATER F OR 15 MIN & CONTACT A DR.WASH CONTAMINATED CLO.

Flash Point:23 F TCC -5C

Extinguishing Media:FOAM, DRY CHEMICAL, WATER SPRAY FOG OR CO*2 Fire Fighting Procedures:USE AIR SUPPLIED EQPMT FOR ENCL AREAS.COOL EXPOS CONTAIN W/W

Unusual Fire/Explosion Hazard: KEEP AWAY FROM HEAT, SPARKS & FLAME.

======== Accidental Release Measures

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAME,ELECTRICAL,STATIC OR FRICTIONAL SPARKS;HOT SURFACES,ETC).AVOID BREATHING VAPORS.VENTILATE AREA.CONTAIN & SCOOP UP SPILL W/NON-SPARKING TOOLS,RAGS,ETC.USE INERT AB SORB MATER ON SM SPILLS OR ON RESIDUALSOF LG SPI

Handling and Storage Precautions: KEEP CONTAINERS CLOSED & UPRIGHT TO PREVENT LEAKAGE. AVD FLAMES, WELDING, SMOKING, SPA RKS, OPEN

LIGHTS, ETC. AVD BREATHING OF VAP OR SPRAY MIST. AVD EYE & SK Other Precautions: MAINTAIN GOOD PERSONAL HYGIENE. DO NOT USE IN CONFINED AREAS, TANK OR PIT W/O ADEQUATE VENTILATIONS.

Respiratory Protection:ORGANIC VAP CANISTER WHERE OXYGEN CONTENT IS ADEQ & VAP CONCENTR IS Ventilation:LOC EXHAUST-YES, MECHANICAL-YES Protective Gloves:RUBBER GLOVES Eye Protection:GOGGLES Supplemental Safety and Health ADDTL HAZ.I NGRED:N. BUTYL ACETATE E00720000,5.0% 150PPM;ISOPROPYL ALCOHOL,NT8050000,3.5%,400PPM.

HCC:F2 Vapor Density:HEAV Spec Gravity:WT/GL Evaporation Rate & amp; Reference:N. BUTYLACET-FAST Solubility in Water:NEGLIGIBLE Appearance and Odor:VISCOUS BLK LIQUID W/TYPICAL SOLVENT ODOR. Percent Volatiles by Volume:74

Stability Indicator/Materials to Avoid:YES

====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE W/LOCAL APPLICABLE REGS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document shou

Id seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.