

PRATT & LAMBERT -- ENAMEL ALKYD -- 8010-00-527-2628

=====
Product Identification
=====

Product ID:ENAMEL ALKYD

MSDS Date:01/01/1985

FSC:8010

NIIN:00-527-2628

MSDS Number: BFCVV

=== Responsible Party ===

Company Name:PRATT & LAMBERT

Emergency Phone Num:800-424-9300, NITE

CAGE:PRATT

=== Contractor Identification ===

Company Name:PRATT & LAMBERT

Address:250 PETTIT AVE

Box:2153

City:BELLMORE

State:NY

ZIP:11710

Country:US

Phone:800-647-2253

CAGE:PRATT

Company Name:PRATT AND LAMBERT INC

Address:945 BURLINGTON

Box:206

City:KANSAS CITY

State:MO

ZIP:64141

Country:US

CAGE:92216

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 30%

OSHA PEL:100 PPM

=====
Hazards Identification
=====

Effects of Overexposure:INH: RESP TRACT IRRIT, NERVOUS SYSTEM D

EPRESS,
SKIN/EYE IRRIT.

=====
First Aid Measures
=====

First Aid:FLUSH EYES/SKIN W/WATER. REMOVE CONTAM CLOTHING. REMOVE TO FRESH AIR. CALL MD IF NEC.

=====
Fire Fighting Measures
=====

Flash Point:104F, 40C TCC

Lower Limits:1.10

Extinguishing Media:C02, FOAM, DRY CHEM, POLYMER FOAM

Fire Fighting Procedures:SELF-CNTND BRTHNG APPARATUS. WATER - USE FOG NOZZ

Unusual Fire/Explosion Hazard:ISOLATE FROM HEAT, ELEC TRICAL EQUIP, OPEN

FLAME, CLOSED CNTNRS MAY EXPLODE WHEN VERY HOT.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. VENT AREA. REMOVE W/INERT ABSORBENT, NONSPARKING TOOLS.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F

Other Precautions:GROUND CNTNRS WHEN POURING. AVOID EXCESS FREE FALL OF LIQ. DO NOT FLAMECUT, BRAZE, WELD W/O RESP & VENT. ADD LABEL

WARNING. DO NOT TAKE INTERN.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:OUTDOORS, USE MECH FILTER RESP. INDOOR, CHEM MECH.

Ventilation:GEN DILUTION OR LOCAL EXHST

Protective Gloves:REQ

Eye Protection:SPLASH GOGGLES

Other Protective Equipment:PREVENT PROLONGED SIN CNTCT W/CONTAM CLOTHING

Supplemental Safety and Health

EMER DAY #316-733-1361. BOILING RANGE: 155-189.4C. RESP PROT: CONFINED AREAS USE AIRLINE TYPE RE

SP.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:311-373F

Vapor Pres:32

Evaporation Rate & Reference: