

EASTMAN KODAK CO. -- 146 4114,RAPID FIXER,PART A -- 6750-00-528-0473

===== Product Identification =====

Product ID:146 4114,RAPID FIXER,PART A

MSDS Date:10/29/1987

FSC:6750

NIIN:00-528-0473

Kit Part:Y

MSDS Number: BFCYQ

=== Responsible Party ===

Company Name:EASTMAN KODAK CO.

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-722-5151

Emergency Phone Num:716-7

22-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:AMMONIUM THIOSULFATE

CAS:7783-18-8

RTECS #:XN6465000

Minumum % Wt:40.

Maxumum % Wt:50.

Ingred Name:SODIUM ACETATE

CAS:126-96-5

RTECS #:AJ4375000

Minumum % Wt:5.

Maxumum % Wt:10.

Ingre

d Name:BORIC ACID  
CAS:10043-35-3  
RTECS #:ED4550000  
< Wt:5.

Ingred Name:WATER  
CAS:7732-18-5  
RTECS #:ZC0110000  
Minumum % Wt:40.  
Maxumum % Wt:50.

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:PRODUCT IS IRRITATING TO EYES. IT IS  
VERY UNLIKELY TO BE MISTED FOR INHALATION. MFR STATES IT IS LOW  
INGESTION HAZARD.  
Effects of Over  
exposure:EYE:IRRITATION. SKIN/INGESTED/INHALED:NOT  
KNOWN;EXPECTED TO BE LOW HAZARD.FOR USUAL INDUSTRIAL HANDLING.  
Medical Cond Aggravated by Exposure:NONE

===== First Aid Measures =====

First Aid:EYE:FLUSH WITH WATER. MFR SAYS NOTHING ELSE. HMIS: SKIN:WASH  
WITH SOAP & WATER. INHALED:REMOVE FROM EXPOSURE. INGESTION:GET  
MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:NONE  
Extinguishing Media:U  
SE AGENT APPROPRIATE FOR SURROUNDING FIRE.  
Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS.  
Unusual Fire/Explosion Hazard:MAY EMIT TOXIC FUMES UNDER FIRE  
CONDITIONS.

===== Accidental Release Measures =====

Spill Release Procedures:MFR STATES "FLUSH TO DRAIN WITH LARGE AMOUNTS  
OF WATER".  
Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE TIGHTLY CLOSED,AWAY FROM

STRONG  
ALKALI.

Other Precautions:READ PRECAUTIONARY/LABEL ON THE CONTAINER BEFROE USE.  
KEEP OUT OF THE REACH OF CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY NEEDED.  
Ventilation:NORMAL ROOM VENTILATION SHOULD BE SUFFICIENT.  
Protective Gloves:IMPERVIOUS IF PROLONGED/REPEATED CONTACT  
Eye Protection:SAFETY GLASSES.  
Other Protective Equipment:AS NECESSARY TO PREVENT SKIN CONTACT.  
Work Hygienic Practices:USE NORMAL CHEMIC  
AL HYGIENE PRACTICES.  
Supplemental Safety and Health  
KEY1:N1 PART A OF A TWO PART KIT.

===== Physical/Chemical Properties =====

HCC:C2  
Boiling Pt:>100.C, 212.F  
Vapor Pres:18  
Vapor Density:0.6  
Spec Gravity:1.318  
pH:5.0  
Solubility in Water:COMPLETE  
Appearance and Odor:CLEAR,LIGHT YELLOW SOLUTION,SLIGHT SULFUR  
DIOXIDE/ACETIC ACID ODOR.  
Percent Volatiles by Volume:50

===== Stability and Reactivity Data =====

Stability Indicator/Materials  
to Avoid:YES  
STRONG ALKALI.  
Stability Condition to Avoid:NONE  
Hazardous Decomposition Products:NORMAL PRODUCTS OF COMBUSTION,OXIDES  
OF NITROGEN AND SULFUR,AMMONIA.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE I/A/W FEDERAL,STATE,LOCAL REGULATIONS.  
MFR SUGGESTS FLUSH TO DRAIN WITH LARGE AMOUNTS OF WATER.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of th

e Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.