

INSULATING MATERIALS INC -- A7526F ADHESIVE:CLYPTAL RESIN -- 8040-00-530-4820

=====  
Product Identification  
=====

Product ID:A7526F ADHESIVE:CLYPTAL RESIN

MSDS Date:01/01/1987

FSC:8040

NIIN:00-530-4820

MSDS Number: BFDBG

=== Responsible Party ===

Company Name:INSULATING MATERIALS INC

Address:1 CAMPBELL RD

City:SCHENECTADY

State:NY

ZIP:12306

Country:US

Info Phone Num:518-395-3310

Emergency Phone Nu

m:518-395-3310

CAGE:08800

=== Contractor Identification ===

Company Name:INSULATING MATERIALS INC

Address:1 CAMPBELL RD

Box:1404

City:SCHENECTADY

State:NY

ZIP:12306-9701

Country:US

Phone:518-395-3300

CAGE:08800

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

OSHA PEL:100 PPM

===== Hazards Identification =====

Effects of Overexposure:NAUSEA, DIZZINESS, & MILD SKIN SENSITIZATION.

===== First Aid Measures =====

First Aid:INHALATION:MOVE TO FRESH AIR. EYES:IMMEDIATELY FLUSH W/WATER FOR AT LEAST 15 MIN. CALL MD. SKIN:WIPE MATERIAL OFF W/DRY RAGS. WAS W/MILD SOAP & WATER.

===== Fire Fighting Measures =====

Flash Point

Method:COC

Flash Point:50.0F,10.0C

Extinguishing Media:FOAM,CO\*2,DRY CHEMICAL

Fire Fighting Procedures:NONE REQUIRED

Unusual Fire/Explosion Hazard:KEEP AWAY FROM FLAME & SPARKS

===== Accidental Release Measures =====

Spill Release Procedures:WIPE UP W/DRY RAGS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT BREATHE VAPORS EXCESSIVELY. AVOID SKIN OR EYES CONTACT.

Other Precautions:AVOID SPARKS & OPEN FLAME.

===== Exposure Controls/Personal Protection =====

Ventilation:LOCAL EXHAUST-PREFERED.MENCHANICAL-TO CONTROL SOLVENT VAPOR

Eye Protection:SAFETY GLASSES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Spec Gravity:0.96

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BLUE, THIN LIQUID/SOLVENT ODOR.

Percent Volatiles by Volume:60

===== Stability and Reactivity Data =====

Stability

Indicator/Materials to Avoid: YES  
NONE

===== Disposal Considerations =====

Waste Disposal Methods: MFG RECOMMENDS BURN & BURY IN LANDFILL. DISPOSE  
IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to  
be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.