

KOPPERS COMPANY,INC. -- LACQUER CAMOUFLAGE -- 8010-00-530-5326

=====
Product Identification
=====

Product ID:LACQUER CAMOUFLAGE

MSDS Date:01/01/1985

FSC:8010

NIIN:00-530-5326

MSDS Number: BFDBP

=== Responsible Party ===

Company Name:KOPPERS COMPANY,INC.

Emergency Phone Num:412-227-2000

CAGE:EO463

=== Contractor Identification ===

Company Name:FEDERAL SPECIFICATIONS, PROMULGATED BY GSA

Box:City:WA

SHINGTON

State:DC

Country:US

CAGE:81348

Company Name:KOPPERS COMPANY, INC.

CAGE:EO463

=====
Composition/Information on Ingredients
=====

Ingred Name:TCP

RTECS #:WX4900000

Fraction by Wt: 3%

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 3%

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:N. BUTANOL

RTECS #:EK8750000

Fraction by Wt: 5%

ACGIH TLV:50PPM

Ingred Name:METHYL ISOBUTYL KETONE (HEXONE) (SARA III)

CAS:10

8-10-1
RTECS #:SA9275000
Fraction by Wt: 6%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:50 PPM/75 STEL; 9394
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 12%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM
ACGIH TLV:200 PPM/300STEL;9394
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Effects of Overexposure
:SYSTEMIC TOXI EFFECTS MAY ALSO RESULT FROM SKIN
ABSORPTION.IRRITATION TO EYES,NOSE AND THROAT NEAR O

=====
===== First Aid Measures =====

First Aid:IF INHALED,REMOVE TO FRESH AIR.IF NOT BREATHING,GIVE
ARTIFICIAL RESPIRATION,PREFERABLY MOUTH TO MOUTH CALL A
PHYSICIAN.IN CASE OF SKIN CONTACT,WASH THOROUGHLY WITH SOAP AND
WATER;FOR EYES FLUSH IMMEDI ATELY WITH PLENTY OF WATER FOR 15
MIN.AND CONTACT.

=====
===== Fire Fighting Measure

s =====

Flash Point:23 F TCC -5 C
Extinguishing Media:FOAM,DRY CHEMICAL,WATER SPRAY FOG OR CO*2
Fire Fighting Procedures:USE AIR SUPPLIED EQUIPMENT FOR ENCLOSED
AREAS.COOL EXPOSED
Unusual Fire/Explosion Hazard:KEEP AWAY FROM HEAT, SPRAKS AND FLAME.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF
IGNITION(FLAME,ELECTRICAL,STATIC OR FRICTIONAL SPARKS;HOT
SURFACES,ETC.)AVOID BREATHING VAPORS.VENTILATE

AREA.CONTAIN AND

SCOOP UP SPILL WITH NON-SPARKING TOOLS,RAGS,ETC.USE INER T
ABSORBENT MATERIALS ON SMALL SPILLS OR ON RESI

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED AND UPRIGHT TO
PREVENT LEAKAGE.AVOID FLAMES,WELDING,SMOKING,SPARKS,OPEN
LIGHTS,ETC.AVOID BREATHING OF VAPOR OR SPRAY MIST.AVOID

Other Precautions:MAINTAIN GOOD PERSONAL HYGIENE,DO NOT USE IN CONFINED
AREAS,TANK OR PIT WITHOUT ADEQ
UATE VENTILATION.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:ORGANIC VAPOR CANISTER WHERE OXYGEN CONTENT IS
ADEQUATE AND VAPOR CO

Ventilation:YES

Protective Gloves:RUBBER GLOVES

Eye Protection:GOGGLES

Supplemental Safety and Health

N.BUTYL ACETATE E00720000 6% TLV 150PPM; VM AND P NAPHTHA

SE7555000,5%TLV 300PPM; ALKYD-NITROCELLULOSE AMSCO 6645 SOLVENT

=====
Physical/Chemical Properties
=====

HCC:F3

Evaporation

Rate & Reference:N.BUTYL ACET-FASTE

Appearance and Odor:WHITE VISCOUS LIQUID WITH TYPICAL SOLVENT ODOR.

Percent Volatiles by Volume:72%

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

=====
Disposal Considerations
=====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL APPLICABLE
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This informatio

n is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.