View NSN Online: https://aerobasegroup.de/nsn/8010-00-530-5563

AMERON INDUSTRIAL COATINGS DIVISION -- GREEN #14260 -- 8010-00-530-5563

========= Product Identification ==============

Product ID:GREEN #14260 MSDS Date:01/01/1987

FSC:8010

NIIN:00-530-5563

MSDS Number: BFDBS === Responsible Party ===

Company Name: AMERON INDUSTRIAL COATINGS DIVISION

Address: 201 N BERRY ST

City:BREA State:CA

ZIP:92621-3904 Country:US

Info Phone Num:714-529-4597

Emergency Phone Num:714-529-4597

CAGE:09869

=== Contractor Identification ===

Company Name: AMERON INDUSTRIAL COATINGS DIVISION

Address: 201 N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904 Country:US

Phone:714-529-4597

CAGE:09869

======= Composition/Information on Ingredients ========

Ingred Name: NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000 Fraction by Wt: 45.0% OSHA PEL:100 PPM

========== Hazards Identification ===============

Effects of Overexposure: ANESTHETIC, IRR.

NERVOUS SYS. DEPRESSION, EYE & SKIN IRRITATION
======================================
First Aid:IN CASE OF CONTACT FLUSH SKIN AND EYES WITH WATER AND REMOVE CONTAMINATED CLOTHING. IF INHALED REMOVE TO FRESH AIR. CALL A PHYSICIAN IF CONDITIONS PERSIST
======================================
Flash Point:85F TCC Lower Limits:1.1 Extinguishing Media:SMALL FIRES-CARBON DIOXIDE OR DRY CHEM. LARGE
FIRES-FOAM Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS FOR FIREMEN Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE
======== Accidental Release Measures ==========
Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS
========== Handling and Storage ============
Handling and Storage Precautions:DO NOT STORE ABOVE 12 0F. STORE LARGE
QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE FLAMMABLES.
Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES
====== Exposure Controls/Personal Protection ========
Respiratory Protection:USE NIOSH APPROVED PAINT RESPIRATOR OR AIR SUPPLIED RESPIRATOR Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST AS NECESSARY Supplemental Safety and Health RESPIRATOR USE BASED ON C

OF RESPIRATORY TRACT OR ACUTE

HEM. AND CONDITIONS OF USE ========= Physical/Chemical Properties =========== HCC:F3 Boiling Pt:B.P. Text:311-375F Vapor Density:>1 Evaporation Rate & Evaporation R Percent Volatiles by Volume:62.0 ========= Stability and Reactivity Data ============= Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid: AVOID FIRE, HEAT AND HOT SURFACES ======= Disposal Considerations ============ Waste Disposal Meth

ods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional adv ice to verify and assume responsibility for the suitability of this information to their

particular situation.