

EVERSEAL MFG CO INC -- TYPE 1,WHITE -- 8030-00-550-8017

===== Product Identification =====

Product ID:TYPE 1,WHITE

MSDS Date:01/01/1987

FSC:8030

NIIN:00-550-8017

MSDS Number: BFDXX

=== Responsible Party ===

Company Name:EVERSEAL MFG CO INC

Address:475 BROAD AVE

City:RIDGEFIELD

State:NJ

ZIP:07657-2329

Country:US

Info Phone Num:201-943-4986 / FAX 201-943-1123

Emergency Phone Num:201-943-4986

CAGE:72

988

=== Contractor Identification ===

Company Name:EVERSEAL MFG CO INC

Address:475 BROAD AVE

Box:City:RIDGEFIELD

State:NJ

ZIP:07657-2329

Country:US

Phone:201-943-4986

CAGE:72988

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

OSHA PEL:100 PPM

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 15.0%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name

:CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS:1317-65-3

RTECS #:EV9580000

Fraction by Wt: 45.0%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:ALKYD RESIN

Fraction by Wt: 2.0%

===== Hazards Identification =====

Effects of Overexposure:DRYING OF SKIN,EYE IRRITATION,EXCESSIVE  
INHALATION MAY CAUSE ANESTHESIA,HEADACHE,DIZZINESS,NAUSEA

===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH  
AIR,APPLY ARTIFICAL RESPIRATION IF  
NECESSARY,CALL A PHYSICIAN.SKIN CONTACT:WASH WITH MILD SOAP AND  
WATER APPLY A MILD CREME,IN SEVERE CASES CONTACT A  
PHYSICIAN,INGESTION: CA LL A PHYSICIAN

===== Fire Fighting Measures =====

Flash Point:105F TCC

Lower Limits:0.9

Upper Limits:6.0

Extinguishing Media:EXCLUDE AIR-USE FOAM,CO2,STEAM,DRY CHEMICAL

Fire Fighting Procedures:SUPPLY AIR OR SELF CONTAINED BREATHING  
APPARATUS

Unusual Fire/Explosion Hazard:W

ATER MAY BE UNSUITABLE EXCEPT FOR  
COOLING EFFECTS

===== Accidental Release Measures =====

Spill Release Procedures:FLUSH WITH WATER INTO RETAINING AREA OR  
CONTAINER.AVOID SPARKS.FIRE OR HOT METAL SURFACES,SMALL QUANTITIES  
MAY BE ABSORBED ONTO AN APPROPRIATE ABSORBANT.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP COOL & AWAY FROM SOURCE OF  
IGNITION. USE WITH ADEQUATE VENTILATION. AVOID PRO

LONGED OR  
REPEATED PERSONAL CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH RECOMMENDED RESPIRATOR-DEPENDS ON  
CONCENTRATION ABOVE TWA  
Ventilation:WHATEVER IS SUFFICIENT TO KEEP WORK ROOM CONCENTRATION  
Protective Gloves:IMPERMEABLE  
Eye Protection:CHEMICAL GOGGLES  
Other Protective Equipment:APRON, BARRIER CREAM  
Supplemental Safety and Health  
CHLORINATED LONG CHAIN PARAFFINS 17 PERCENT

===== Physical/Chemical Properties =====

HCC:F4  
Boiling Pt:B.P. Text:326-387F  
Vapor Pres:5  
Vapor Density:4.9  
Spec Gravity:1.62  
Evaporation Rate & Reference:SLOWER THAN NBUACT  
Appearance and Odor:STANDARD PAINT ODOR  
Percent Volatiles by Volume:42.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG, OXIDIZING AGENTS  
Stability Condition to Avoid:HEAT,SPARK OPEN FLAME,FIRE  
Hazardous Decomposition Products:THEMAL DECOMPOSITION MAY YIELD CARBON  
MONOXIDE AND CO2

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE UNDER SAFE CONDITIONS OR DISPOSE OF  
IN ACCORDANCE WITH APPLICABLE LOCAL,STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be

accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.