View NSN Online: https://aerobasegroup.de/nsn/8030-00-550-8628

Product ID:DAP BUTYL GUTTER & LAP SEALANT MSDS Date:01/01/1987 FSC:8030 NIIN:00-550-8628 **MSDS Number: BFDYF** === Responsible Party === Company Name: D A P INC Address:5300 HUBERVILLE ROAD Box:277 **City:DAYTON** State:OH ZIP:45401-0277 Country:US Info Phone Num:513-236-0911 Emergency Phone Num:513-236-0911 **CAGE:**IO869 === Contractor Identification === Company Name: D A P INC

Company Name:D A P INC Box:277 City:DAYTON State:OH ZIP:45411-0277 Country:US Phone:800-543-3840 CAGE:I0869 Company Name:DAP INC. Address:Box:277 City:DAYTON State:OH ZIP:45401-0277 Country:US Phone:513-253-7154/800-543-3840 CAGE:90300

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN) CAS:8030-30-6 RTECS #:SE7555000 Fraction by Wt: 1-10% OSHA PEL:100 PPM

Ingred Name: VM & P NAPHTH

A CAS#8030-30-6 RTECS #:QI9458000 Fraction by Wt: 1-5% ACGIH TLV:300 PPM

Ingred Name:TITANIUM DIOXIDE CAS:13463-67-7 RTECS #:XR2275000 Fraction by Wt: 0-2% OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Effects of Overexposure:ACUTE:LIQ,VAP IRRIT EYE,SKIN,RESPIR TRACT.MAY CAUSE CENTRAL NERV SYST DEPRESS:HDCH,DIZZ,FAT,NAUS.SUP

First Aid:INHAL:R EMOVE TO FRESH AIR.RESTORE BREATH IF NECESSARY.GET MD.EYE:FLUSH W/ LARGE AMONTS OF WATER FOR 15 MIN.CONTACT A PHYSICIAN.SKIN:WASH W/ SOAP & WATER.GET MD IF IRRIT DEVELOPS.INGEST;DO NOT INDUCE V OMIT.GIVE H*20,MILK.CONTACT A MD IMMEDIATELY

Flash Point:58F,14C TCC Extinguishing Media:FOAM,CO*2,DRY CHEMICALS Fire Fighting Procedures:COOL CONTNR W/ H*20 DO NOT USE STRAIGHT HOSE STREAM.USE SCBA Unusual Fire/Exp Iosion Hazard:CONTNR MAY EXPLO IF EXPO TO EXTREME HEAT.ISOLATE FROM IGNIT SOURC.DO NOT PUT IN CONTACT W/ OXIDI HAT

Spill Release Procedures:LARGE:USE PROTECT EQUIP.ELIMINATE ALL SOURCES OF IGNIT,VENTILATE SPILL AREA.CONTAIN SPILL BY DIKING.ABSORB SPILL W/ ABSORBT MATRL.SHOVEL INTO CONTNR.CLEAN UP REMAINING W/ A NONFLAM SOLVENT:1,1,1-TRICH LOROETHANE.PREVENT RUN-OFF TO STREAM,SEWERS.SUPP

Handling and Storage Precautions:KEEP CONTNR FROM HEAT,FLAMES,DIRECT SUNLIGHT.DO NOT STORE AT TEMP ABOVE 120F.PROVIDE CROSS VENT IN STORAGE AREA.AVOID PRLG/RPTD BREATH,SKIN CONTACT
Other Precautions:KEEP CONTNR TIGHTLY CLOSED WHEN NOT IN USE.CONTAINS FLAMM SOLVENT.VAP HARMF,MAY CAUSE FLASH FIRE.HARM OR FATAL IF SWALLOWED.USE ONLY W/ ADEQUATE VENT & ELIMINATE SOURCES OF IGNITION.WASH CLOTH

Respiratory Protection:NIOS/MSHA APPROVD RESPIRATOR IF TLV EXCEEDED. Ventilation:MECHANICAL VENT(LOCAL OR GENERAL EXHAUST) TO KEEP BELOW TLV.

Protective Gloves: IMPERVIOUS

Eye Protection: GOGG W/ SIDE SHIELDS

Other Protective Equipment: EYE WAS & SOLVENT IMPERV APRON. BARRIER CREAM MAY BE USED

Supplemental Safety and Health

MSDS PREP:17MAY86.SPEC:TYPE 2,CLASS A.BP:100-200C.OVEREXPO:INGEST:CAUSE NAUSEA,VOMIT,DIARR,DEPRESS RESPIRATION.IN CASE OF SPILL:NOTIFY

LOCAL HEALTH OFFIC.SMALL:USE ABSORB MAT, PLACE INTO CONTNR

HCC:F2 Boiling Pt:B.P. Text:212-392F Spec Gravity:1.46 Evaporation Rate & amp; Reference:N/K(PER MFR) Solubility in Water:NEGLIGIBLE Appearance and Odor:OPAQUE PASTE W/ A PETROLEUM DISTILLATE ODOR Percent Volatiles by Volume:15.0

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS AND CAU

STICS Stability Condition to Avoid:EXCESSIVE HEAT Hazardous Decomposition Products:NORMAL CONBUSTION PRODUCTS,I.E.CO*X,NO*X

Waste Disposal Methods:DISCARDED SPILL RESIDUE MAY BE INCINERATED.DO NOT INCINERATE SEALED CONTAINERS.DISPOSE ACCORDING TO FEDERAL,STATE AND LOCAL REGULATIONS.LIQUID CAN NOT BE DISPOSED OF IN A LANDFILL.

Disclaimer (provided with this information by the compiling agencies): This information

is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.