

PPG INDUSTRIES,INC. -- TRI-ETHANE 366 -- 6810-00-551-1487

=====
Product Identification
=====

Product ID:TRI-ETHANE 366

MSDS Date:10/05/1988

FSC:6810

NIIN:00-551-1487

MSDS Number: BFDYX

=== Responsible Party ===

Company Name:PPG INDUSTRIES,INC.

Address:1-PPG PLACE

City:PITTSBURGH

State:PA

ZIP:15272

Country:US

Info Phone Num:304-843-1300

Emergency Phone Num:304-843-1300

Preparer's Name:R. KENNETH L

EE

CAGE:GO796

=== Contractor Identification ===

Company Name:PPG INDUSTRIES INC

Address:ONE PPG PLACE

Box:City:PITTSBURGH

State:PA

ZIP:15272

Country:US

Phone:1-800-245-2974 (CAL HYPO)

CAGE:47695

Company Name:PPG INDUSTRIES,INC. COATINGS TRESINS DIV.

Address:1 PPG PL

City:PITTSBURGH

State:PA

ZIP:15272

Country:US

CAGE:GO796

Company Name:SHIELDING SYSTEMS CORP

CAGE:49942

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SA

RA III)
CAS:71-55-6
RTECS #:KJ2975000
Fraction by Wt: 96.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:350 PPM
ACGIH TLV:350 PPM/450STEL;9394
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS
Ozone Depleting Chemical:1

Ingred Name:1,4-DIOXANE (DIETHYLENE DIOXIDE) (SARA III)
CAS:123-91-1
RTECS #:JG8225000
OSHA PEL:S, 100 PPM
ACGIH TLV:S, 25 PPM; 9293
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:GLYCOL METHYLENE ETHER
CAS:646-06-0
RTECS #:JH6760000

Ingred Name:SEC-BUTYL ALCOHOL (SARA III)
CAS:
78-92-2
RTECS #:EO1750000
OSHA PEL:150 PPM
ACGIH TLV:100 PPM; 9293

Ingred Name:OTHER STABILIZERS

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 RAT ORAL10-12G/KG;DERMAL RAB:15G/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:IRRITATION OF
EYES,SKIN,RESPIRATORY OR G.I. TRACT,CNS EFFECTS LIKE
HEADACHE,DIZZINESS,NAUSEA,LOSS OF CO-ORDINATION.

CHRONIC:DERMATITIS.

Explanation of Carcinogenicity:DATA PER MSDS.

Effects of

Overexposure:INHALE:DIZZINESS,NAUSEA,UNCONSCIOUSNESS.SKIN/EYE:IRRITANT.INGEST:IRRITATION OF THE MOUTH.

Medical Cond Aggravated by Exposure:NO DATA AVAILABLE.

=====
===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR.GIVE CPR/OXYGEN IF NEEDED.
EYE/SKIN:FLUSH WITH PLENTY OF WATER. INGEST:IF CONSCIOUS,DRINK
LARGE QUANTITIES OF WATER,DO NOT INDUCE VOMIT
ING.TAKE TO A
HOSPITAL;IF UNCONSCIOUS, TAKE IMMEDIATELY TO A HOSPITAL.

=====
===== Fire Fighting Measures =====

Lower Limits:7

Upper Limits:15

Extinguishing Media:CO*2, FOAM, DRY CHEM & H*2O FOG.

Fire Fighting Procedures:WEAR SELF-CNTND BRTHG APP

Unusual Fire/Explosion Hazard:VAPORS CONCENTRATED IN A CONFINED OR
POORLY VENTILATED AREA CAN BE IGNITED WITH A HIGH ENERGY SPARK.

=====
===== Accidental Release Measures =====

Spill Release

Procedures:EVACUATE & VENTILATE THE AREA.STAY UPWIND.WEAR
PROPER PROTECTION.DIKE AREA TO CONTAIN SPILL.AVOID CONTAMINATING
WATER.RECOVER SPILLED MATERIAL ON ABSORBENTS & SWEEP INTO CLOSED
CONTAINERS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT USE IN POORLY VENTILATED OR
CONFINED AREA.KEEP CONTAINER CLOSED.DO NOT STORE OR STACK ALUMINUM
IN CONTACT WITH TRI-ETHANE-POSSIBLE SOLV DECOMPO

Other Precautions:AVOID PR

OLONGED OR REPEATED BREATHING OF VAPOR. AVOID
CONTACT WITH EYES OR PROLONGED/REPEATED CONTACT WITH SKIN. DO NOT
USE IN POORLY VENTILATED OR CONFINED SPACES.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC
VAPORS/MIST IF ABOVE PEL/TLV.

Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV.

Protective Gloves:VITON

Eye Protection:CHEM SPLASH GOGGLES

Other Protective Equipment:PROTECTIVE CLOTHING,EYE-WASH

FACILITIES,BOOTS,APRON.

Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN;DO NOT BREATHE VAPORS/MIST.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:T4

Boiling Pt:B.P. Text:72-88C

Vapor Pres:135

Vapor Density:4.54

Spec Gravity:1.30-1.32

pH:6-7.5

Evaporation Rate & Reference:0.35,ETHER=1

Solubility in Water:NEG.

Appearance and Odor:CLEAR,COLORLESS LIQUID WITH ETHER-LIKE ODOR.

Percent Volatiles by Volume:100

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

CAUSTIC SODA,OXIDIZING MATERIALS.

Stability Condition to Avoid:OPEN FLAMES,HOT SURFACES,ELECTRIC ARCS.

Hazardous Decomposition Products:HCL,TRACES OF PHOSGENE.

===== Disposal Considerations =====

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular

ar situation.