

UNION OIL CO. OF CALIF.;UNION 76 DIV. -- MINERAL SPIRITS 75 -- 8010-00-558-7026
===== Product Identification =====

Product ID:MINERAL SPIRITS 75

MSDS Date:01/01/1985

FSC:8010

NIIN:00-558-7026

MSDS Number: BFFJY

=== Responsible Party ===

Company Name:UNION OIL CO. OF CALIF.;UNION 76 DIV.

Address:1650 EAST GOLF ROAD

City:SCHAUMBURG

State:IL

ZIP:60195

Country:US

Info Phone Num:312-619-2644

Emergency

Phone Num:312-619-2644

CAGE:EO159

=== Contractor Identification ===

Company Name:UNION OIL CO OF CALIFORNIA, CORP. DIV-EASTERN

Address:1650 EAST GOLF ROAD

Box:City:SCHAUMBURG

State:IL

ZIP:60195

Country:US

Phone:708-619-2644

CAGE:77416

Company Name:UNION OIL CO. OF AMERICA,UNION CHEMICALS DIV.

Address:1900 E GOLF ROAD

City:SCHAUMBURG

State:IL

ZIP:60194-5021

Phone:312-490-2500

CAGE:EO159

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS)

OR BENZIN)
CAS:8030-30-6
RTECS #:SE7555000
Fraction by Wt: 100%
OSHA PEL:100 PPM

=====
Hazards Identification
=====

Effects of Overexposure:EYES: SEVERE IRRIT. SKIN: DRYNESS. INH:HDCH,
DIZZ, NAUSEA.

=====
First Aid Measures
=====

First Aid:EYES:FLUSH W/WATER 15 MINS,CALL MD. SKIN:WSH W/MILD SOAP &
WATER,APPLY SKIN CREAM. INH:MOVE TO FRESH AIR & CALL MD. APPLY
ARTIFICIAL RESP IF NEC.

=====
Fire Fighting Measures
=====

Flash Point:108F,42C PCC
Lower Limits:1.0
Upper Limits:6.0
Extinguishing Media:WATER SPRAY, CO*2 FOAM,DRY CHEMICAL.
Fire Fighting Procedures:WEAR SCBA. USE WATER SPRAY TO COOL
FIRE-EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard:A DANGEROUS FIRE HAZARD IF HEATED OR
SPRAYED IN AIR.

=====
Accidental Release Measures
=====

Spill Release Procedures:FLUSHE WITH WATER INTO RETAINING AREA OR
CONTAINER. AVOID EXPOSURE TO SPARKS,FIRE,OR HOT METAL SURFACES.
VENTILATE AREA.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS & OPEN
FLAME. USE WITH ADEQUATE VENTILATION. AVOID PROLONGED OR REPEATED
CONTACT W/SKIN. KEEP CNTNRS CLSD WHEN NOT IN USE.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:SCBA FOR CONCENTRATIONS ABOVE TLV LIMITS.(MFG)
Ventilation:LOCAL EXHAUST
Protective

Gloves: YES

Eye Protection: YES

Other Protective Equipment: EYE BATH AND SAFETY SHOWER.

Supplemental Safety and Health

CONFORMS TO TT-T-291E, TYPE II, GRADE A. BP: 156-198C EVAP
RATE: