View NSN Online: https://aerobasegroup.com/nsn/8010-00-558-7027

Product ID:TT-T-306C THINNER
MSDS Date:01/01/1985 FSC:8010
NIIN:00-558-7027
MSDS Number: BFFKC
=== Responsible Party ===
Company Name:STIC-ADHESIVE PRODUCTS CO, INC.
Emergency Phone Num:213-268-2956
CAGE:59142
=== Contractor Identification === Company Name:STIC-ADHESIVE PRODUCTS CO INC
Addr
ess:3950 MEDFORD ST
Box:City:LOS ANGELES
State:CA
ZIP:90063-1675
Country:US
CAGE:59142
======================================
Ingred Name:PETROLEUM HYDROCARBON BLEND
Fraction by Wt: 100%
ACGIH TLV:105 PPM
======================================
Effects of Overexposure:DRIES SKIN. INHALING MAY CAUSE ANESTHESIA, HEADACHE, DIZZINESS- UPPER RESPIRATORY IRRITATION.
HEADACHE, DIZZINESS- OFFER RESPIRATORT IRRITATION.
======================================
First Aid:INHALATION-MOVE TO FRESH AIR; ARTIFICIAL RESPIRATION IF NECESSARY. CALL DOCTOR. SKIN-WASH WITH SOAP & WATER, APPLY MILD
SKIN CREAM. SEVER CASES CALL. DOCTOR. EYE. FLUSH WITH WATER;CALL
DOCTOR. INGESTI ON-CALL DOCTOR.
======================================
Flash Point:103F, 40C TCC
Extinguishing Media:FOAM, CO, DRY CHEMICALS
Fire Fighting Procedures: SELF-CONTAINED BREATHING APPARATUS. WATE MAY
BE ÜNSÜITABLE

Unusual Fire/Explosion Hazard:A

VOID SPARKS, FIRE OR NOT METAL SURFACES.

Spill Release Procedures: AVOID SPARKS, FIRE OR HOT METAL SURFACES-FLUSH WITH WATER INTO NON-HAZARDOUS RETAINNG AREA OR CONTAINER. SMALL QUANTITIES MAY BE ABSORBED ON APPROPRIATE ABSORBANT. Handling and Storage Precautions: KEEP COOL & AWAY FROM SOURCES OF IGNITION. USE WITH ADEQUATE VENTILATION. Other Preca utions: AVOID PERSONAL CONTACT. WASH OFF SPILLED LIQUID REMOVE WET CLOTHING. Respiratory Protection: DEPENDS ON CONC. ABOVE TIME WEIGLED TLV, CARTRIDGE RESPIRATOR OR MAS Ventilation:SUFFICIENT TO KEEP AREA BELOW TLV. Protective Gloves: IMPERMEABLE Eye Protection: CHEMICAL GOGGLES Other Protective Equipment: IMPERMEABLE APRON, IMPERMEABLE GLOVES OR BARRIER CREAM. Supplemental Safety and Health ======= Physic HCC:F4 Boiling Pt:B.P. Text:314-378F Vapor Pres:2.4 Vapor Density:4.9 Spec Gravity:0.789 Evaporation Rate & amp; Reference: 0.2/BUAC Solubility in Water:NEGLIGIBLE Appearance and Odor:CLEAR, COLORLESS LIQUID Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES STRONG OXIDANTS; STRONG ACIDS & BASES; SELECTED AMINES. Stability Condition to Avoid:HEAT, OPEN FLAMES, F

IRE Hazardous Decomposition Products:MAY YIELD CO OR CO2

Waste Disposal Methods:INCINERATE UNDER SAFE CONDITIONS OR DISPOSE OF IN ACCORDANCE WITH STATE, LOCAL OR FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.