View NSN Online: https://aerobasegroup.de/nsn/6850-00-559-2835

ELDORADO CHEMICAL CO. INC. -- ED-371 -- 6850-00-559-2835

Product ID:ED-371

MSDS Date:01/01/1985

FSC:6850

NIIN:00-559-2835

MSDS Number: BFFKH === Responsible Party ===

Company Name: ELDORADO CHEMICAL CO. INC.

Address:14350 LOOKOUT ROAD

Box:34837

City:SAN ANTONIO

State:TX ZIP:78265 Country:US

Info Phone Num:512-653-9323

Emergency Phone Num:800-531-1088

CAGE:55208

==

= Contractor Identification ===

Company Name: ELDORADO CHEMICAL COMPANY, INC.

Address:14350 LOOKOUT ROAD

Box:34837

City:SAN ANTONIO

State:TX

ZIP:78265-4837 Country:US

Phone:800-531-1088/210-653-2060

CAGE:55208

======= Composition/Information on Ingredients ========

Ingred Name: ETHANOLAMINE

CAS:141-43-5

RTECS #:KJ5775000 Fraction by Wt: 5%

OSHA PEL:3 PPM/6 STEL

ACGIH TLV:3 PPM/6 STEL; 9192

Ingred Name: CRESOL, ALL ISOMERS (CRESYLIC ACID) (SARA III)

CAS:1319-77-3

RTECS #:GO5950000

DOT Rpt Qty:1000 LBS ========== Hazards Identification =============== Effects of Overexposure: INH: NAUSEA. SKIN: DEFATTING/AMINE RASH. EYES: IRRIT. First Aid:INH:REMOVE TO FRESH AIR. SKIN:WASH W/ SOAP & WATER. EYES:FLUSH W/ WATER FOR 15 MIN;SEE MD. Flash Point:235 F;113C (COC) Extinguishing Media:CO*2,FOAM Fire Fighting Procedures: NONE Unusual Fire/Explosion Hazard:NONE Spill Release Procedures: TAKE UP W/ OIL ABSORBENT MATERIAL & BURY IN SANITARY LANDFILL. SMALL AMOUNTS MAY BE FLUSH TO SEWAGE SYSTEM W/ WATER. ====== Exposure Controls/Personal Protection ======== Respiratory Protection: NOT REQUIRED (MFR) Ventilation:LOCAL EXHAUST-200 CFM TO KEEP BELOW TLV Protectiv e Gloves:RUBBER Eye Protection: FACE SHIELD Other Protective Equipment: RUBBER APRONS & BOOTS Supplemental Safety and Health OTHER EMERGENCY PHONE: 512-494-5337, SPEC: TYPE II, CONTAINER: 55 GAL CAN. ========= Physical/Chemical Properties =========== HCC:B3 Boiling Pt:B.P. Text:270F;132C Vapor Pres:1 Spec Gravity:0.9 Evaporation Rate & Presence: SAME AS WATER Solubility in Water: EMULSIFIERS Appearance and Odor:THIN,AMBER LIQUID Percent Volatiles by Volume:60 ========

OSHA PEL:S, 5 PPM

ACGIH TLV:S, 5 PPM; 9192 EPA Rpt Qty:1000 LBS

Stability Indicator/Materials to Avoid:YES NONE Hazardous Decomposition Products:NONE
====== Disposal Considerations ==========

Waste Disposal Methods:MFR RECOMMENDS: TREATING MATERIAL TO REMOVE NON-VOLATILE HYDROCARBONS & PHENOLICS;FLUSH REMAINDER TO SEWAGE SYSTEM. DISPOSAL METHOD MUST BE IAW FEDERAL, STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies): This i

====== Stability and Reactivity Data =========

nformation is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.