

EVANS MANUFACTURING,INC -- PEEL-COAT B-149 -- 8030-00-582-4598

=====  
Product Identification  
=====

Product ID:PEEL-COAT B-149

MSDS Date:02/05/1991

FSC:8030

NIIN:00-582-4598

MSDS Number: BFGFR

=== Responsible Party ===

Company Name:EVANS MANUFACTURING,INC

Address:1330 SOUTER

City:TROY

State:MI

ZIP:48083

Country:MI

Info Phone Num:313-583-9890

Emergency Phone Num:313-583-9890

Preparer's Name:THOMAS B

EVANS

CAGE:EVANS

=== Contractor Identification ===

Company Name:EVANS MANUFACTURING INC

Address:1330 SOUTER

City:TROY

State:MI

ZIP:48083

Country:US

Phone:313-583-9890

CAGE:EVANS

Company Name:EVANS MFG INC

Address:1330 SOUTER

Box:City:TROY

State:MI

ZIP:48083

Country:US

CAGE:56307

=====  
Composition/Information on Ingredients  
=====

Ingred Name:CELLULOSE ACETATE BUTYRATE

=====  
Hazards Identification  
=====

Effects of Overexposure:NOT APPLICABLE

(MFR)

=====  
===== First Aid Measures =====

First Aid:TREAT SAME AS HOT OIL BURN

=====  
===== Fire Fighting Measures =====

Flash Point Method:OC

Flash Point:400F,204C

Extinguishing Media:CO\*2.

Fire Fighting Procedures:NONE. USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:NONE. TREAT AS OIL FIRE.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:

PRODUCT IS SUPPLIED IN 100% SOLID CARE  
APPROXIMATELY 5 LB IN WEIGHT.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:PRODUCT IS USED TO PROTECT ITEMS IN LONG-TIME STORAGE AT TEMPERATURES FROM 60F TO 180F.

Other Precautions:NONE

=====  
===== Exposure Controls/Personal Protection =====

Ventilation:VENTILATION-IF DESIRED. LOCAL EXHAUST-IF IN ENCLOSED ROOM

Protective Gloves:WHILE DIPPING

Eye Protection:NONE(MFR)

Other Protec

tive Equipment:IF NEEDED CAN USE MILD EXHAUST TO REMOVE FUMES WHEN HOT

Supplemental Safety and Health

=====  
===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>700F,>371C

Spec Gravity:1 (H\*20=1)

pH:NEUT

Solubility in Water:INSOLUBLE

Appearance and Odor:100% SOLID THERMOPLASTIC, WAX LIKE OIL ODOR

Percent Volatiles by Volume:0

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE.

Stabilit

y Condition to Avoid:NONE.

Hazardous Decomposition Products:NONE(MFR)

===== Disposal Considerations =====

Waste Disposal Methods:MFR SUGGESTS DISPOSING SAME AS ANY SOLID PLASTIC. DISPOSE IN ACCORDANCE W/LOCAL,STATE, AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.