

NATIONAL AEROSOL PRODUCTS(DIST)DEVOE&RAYNOLDS(MFR) -- DR039 FLAT ACRYLIC LACQUER #37038 -- 8010-00-582-5382

=====
Product Identification
=====

Product ID:DR039 FLAT ACRYLIC LACQUER #37038

MSDS Date:01/01/1985

FSC:8010

NIIN:00-582-5382

MSDS Number: BFGGM

=== Responsible Party ===

Company Name:NATIONAL AEROSOL PRODUCTS(DIST)DEVOE&RAYNOLDS(MFR)

Address:2193 E 14TH ST

City:LOS ANGELES

State:CA

ZIP:900

21-2843

Country:US

CAGE:5N005

=== Contractor Identification ===

Company Name:NATIONAL AEROSOL PRODUCT

Address:2193 E 14TH ST

Box:City:LOS ANGELES

State:CA

ZIP:90021-2843

Country:US

CAGE:5N005

=====
Composition/Information on Ingredients
=====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 2.90%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA III)

C

AS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 24.0%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 21.0%
OSHA PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 19.0%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PP
M/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:2-BUTOXYETHANOL
CAS:111-76-2
RTECS #:KJ8575000
Fraction by Wt: 7.0%
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293

=====
===== Hazards Identification =====

Effects of Overexposure:INHAL:HEADACHE,NAUSEA,DIZZINESS,SKIN
CONTACT:PROLONGED OR REPEATED CONTACT MAY CAUSE IRRITATION.

=====
===== First Aid Measures =====

First Aid:INHAL:MOVE TO FRESH AIR.SKIN CONTACT-FLU

SH W/LG AMOUNTS OF
WATER.REMOVE CONTAMINATED CLOTHING.EYE CONTACT-FLUSH W/CLEAN WATER
FOR AT LEAST 15 MIN.CALL PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:43 F PMCC
Extinguishing Media:CARBON DIOXIDE,DRY CHEMICAL,FOAM
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS TO BE WORN
BY FIREFIGHTER
Unusual Fire/Explosion Hazard:WATER SHOULD BE USED TO COOL CONTAINERS
EXPOSED TO FIRE

===== Accidental Release Meas
ures =====

Spill Release Procedures:AVOID BREATHING VAPORS,EXTINGUISH IGNITION
SOURCE IN IMMEDIATE AREA.AVOID CONTACT W/LIQUID -MFR RECOMMENDATION

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE AT ELEVATED TEMPERATURES
Other Precautions:CLOSE CONTAINERS AFTER USE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR DEVICE IN
CONFIN
ED AREAS.
Ventilation:SUFFICIENT LOCAL EXHAUST TO KEEP CONCENTRATION BELOW TLV
Protective Gloves:SOLVENT RESIST
Other Protective Equipment:NORMAL PROTECTIVE CLOTHING
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V3
Boiling Pt:B.P. Text:176-343F
Spec Gravity:1.04
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:SLIGHT
Appearance and Odor:BLACK,MOBILE LIQUID CONTAINING VOLATILE SOLVENTS.
Percent Volatiles by Volume:8

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
OXIDIZING MATERIALS, SOFTENS RUBBER
Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN CLOSED CONTAINERS AWAY FROM
IGNITION SOURCES. -MFR RECOMMENDATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for
or use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.