

WITCO CHEMICAL CORP SOUTHWEST PETRO-CHEM INC DIV -- SE 861 0646 HYDRAULIC FLUID --
9150-00-582-5480

===== Product Identification =====

Product ID:SE 861 0646 HYDRAULIC FLUID

MSDS Date:11/13/1990

FSC:9150

NIIN:00-582-5480

MSDS Number: BFGGZ

=== Responsible Party ===

Company Name:WITCO CHEMICAL CORP SOUTHWEST PETRO-CHEM INC DIV

Address:220 W WATERMAN ST

Box:1282

City:WICHITA

State:KS

ZIP:67201

Coun

try:US

Info Phone Num:913-782-5800

Emergency Phone Num:913-782-5800, CHEMTREC 800-424-9300

CAGE:7A506

=== Contractor Identification ===

Company Name:WITCO CHEMICAL CORP SOUTHWEST PETRO-CHEM INC DIV

Address:220 W WATERMAN ST

Box:1282

City:WICHITA

State:KS

ZIP:67201

Country:US

Phone:913-782-5800

CAGE:7A506

===== Composition/Information on Ingredients =====

Ingred Name:HYDRAULIC FLUID,PETROLEUM BASE

Fraction by Wt: UNK

Ingred Name:ADDITIVES(TYPE NOT SPECIFIED)-PER SPECIFICATION

Fraction by Wt: UNK

=====
Hazards Identification
=====

Effects of Overexposure:MAY CAUSE SKIN & EYE IRRITATION WITH PROLONGED CONTACT.

=====
First Aid Measures
=====

First Aid:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. SKIN:WASH WITH SOAP & WATER. EYES:FLUSH WITH WATER 15 MIN. KEEP WARM AND QUIET;CALL A PHYSICIAN IMMEDIATELY IF SWALLOWED & FOR EYES.

=====
Fire Fighting Measures
=====

Flash Point:>302F(>150C)-COC

Extinguishing Media:DRY CHEM,CO*2,FOAM,WATER FOG,SAND/EARTH.

Fire Fighting Procedures:WEAR SELF-CNTND BRTHG APP

Unusual Fire/Explosion Hazard:DENSE SMOKE

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE IGNITION SOURCES,VENTILATE AREA WELL.ABSORB WITH VERMICULITE OR OTHER MATERIALS, SUCH AS SAWDUST,RAGS,PAPER & PLACE IN CLOSED CONTAINER. USE NON SPARKING TOOLS. WEAR PROPER PROTECTIVE EQUIPMENT DURING CLEAN UP.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED.PROTECT FROM PHYSICAL DAMAGE.

Other Precautions:AVOID CONTACT WITH EYES AND SKIN;DO NOT BREATHE VAPOR/MIST.WASH THOROUGHLY AFTER EACH USE.

=====
Exposure Controls/Personal Protection
=====

Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION

Protective Gloves:RUBBER

Eye Protection:GOGGLES/FACE SHI

ELD

Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR PROLONGED CONTACT.

Supplemental Safety and Health

MSDS DATED:01/22/86:PRODUCT CODE:SE 861 0646.ITEM IS OF MILITARY SYMBOL 2110 TH UNDER SPEC:MIL-H-17672D;PER MFR,TAKE TLV AS OIL MIST =5MG/CUM.

===== Physical/Chemical Properties =====

HCC:V6

Spec Gravity:0.874

Solubility in Water:NEGLIGIBLE

Appearance and Odor:AMBER COLOR OIL,ODOR OF MINERAL OIL.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS SUCH AS:H*2O*2,CHROMIC ACID,BROMINE

Stability Condition to Avoid:HEAT, IGNITION SOURCES

Hazardous Decomposition Products:IF COMBUSTED, CO*2, CO, TOXIC HYDROCARBS, OTHER TOXIC OXIDES

===== Disposal Considerations =====

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.