

UNION CHEMICALS DIV,UNION OIL COMP. OF CALIFORNIA -- AMSCO SOLV 1420 XYLENE --
6810-00-584-4070

===== Product Identification =====

Product ID:AMSCO SOLV 1420 XYLENE

MSDS Date:01/01/1987

FSC:6810

NIIN:00-584-4070

MSDS Number: BFGQM

=== Responsible Party ===

Company Name:UNION CHEMICALS DIV,UNION OIL COMP. OF CALIFORNIA

Address:1650 EAST GOLF ROAD

City:SCHAUMBURG

State:IL

ZIP:60195

Country:US

Info

Phone Num:312-619-2644

Emergency Phone Num:312-619-2644

CAGE:DO714

=== Contractor Identification ===

Company Name:UNION CHEMICALS DIVISION

Address:1345 NORTH MEACHAM ROAD

Box:7600

City:SCHAUMBURG

State:IL

ZIP:60196

Phone:213-664-2121 OR 800-424-9300

CAGE:DO714

Company Name:UNION OIL CO OF CALIFORNIA, CORP. DIV-EASTERN

Address:1650 EAST GOLF ROAD

Box:City:SCHAUMBURG

State:IL

ZIP:60195

Country:US

Phone:708-619-2644

CAGE:77416

===== Composition/Information on Ingredients =====

I

ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: >98%.

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=====
Hazards Identification
=====

Effects of Overexposure:MAY IRRITATE SKIN & EYES.RESPIRATORY TRACT IRRITATION,LIVER & KIDNEY DAMAGE IN HUMANS,NAUSEA VOMITG.

=====
First Aid Measures
=====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.

=====
Fire Fighting Measures
=====

Flash Point:=-6.7C, 20.F
20-100F

Lower Limits:UNKN

Upper Limits:UNKN

Extinguishing Media:USE FOAM,CO*2 OR DRY CHEMICALS

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA FOR FIRE FIGHTERS.

Unusual Fire/Explosion Hazard:KEEP WORK AREAS FREE OF HOT METAL

SURFACES & OTHER SOURCES OF IGNITION

=====
Accidental Release Measures
=====

Spill Release Procedures:KEEP SOURCES OF IGNITION & HOT SURFACES ISOLATED FROM THE SPILL.FLUSH SPILLED MATERIAL INTO SUITABLE RETAINING AREAS/CONTAINERS.SMALL AMOUNTS OF SPILLED MATERIAL MAY BE ABSORBED INTO AN APPROPRIATE AB SORBANT.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP PRODUCT CONTAINED

INERS COOL, DRY &

AWAY FROM SOURCES OF IGNITION. PROVIDE ADEQUATE VENTILATION.

Other Precautions: DO NOT BREATHE VAPORS. AVOID SKIN & EYES CONTACT. DO NOT SMOKE IN WORK AREA.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS

Ventilation: PROVIDE MECHAN(GEN/LOCAL EXHAUST) VENT TO MAINTN 1.0

Spec Gravity: