

SUN REFINING AND MARKETING CO(MFR)PHIPPS PROD(DIS) -- XYLENE -- 6810-00-584-4070

=====
Product Identification
=====

Product ID:XYLENE

MSDS Date:01/01/1987

FSC:6810

NIIN:00-584-4070

MSDS Number: BFGQP

=== Responsible Party ===

Company Name:SUN REFINING AND MARKETING CO(MFR)PHIPPS PROD(DIS)

Address:1801 MARKET ST.TEN PENN CENTER; 18 FLOOR

City:PHILADELPHIA

State:PA

ZIP:19103

Info Phone Num:215-447-

1852

Emergency Phone Num:215-447-1852

CAGE:8X531

=== Contractor Identification ===

Company Name:SUN REFINING AND MARKETING COMPANY

Address:1801 MARKET ST,TEN PENN CTR

Box:City:PHILADELPHIA

State:PA

ZIP:19103-1699

Country:US

Phone:215-977-6133

CAGE:8X531

=====
Composition/Information on Ingredients
=====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 86.6%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:10

00 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SARA III)

CAS:100-41-4

RTECS #:DA0700000

Fraction by Wt: 12.6%

OSHA PEL:100 PPM/125 STEL

ACGIH TLV:100 PPM/125STEL 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 0.3%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

INCOORDINATION,LOSS OF
BALANCE,RESPIRATOY FAILURE,IRRITATING TO MUCOUS MEMBRANES RESP.TRAC

=====
First Aid Measures
=====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF
NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE MOUTH;
GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER
SYMPTOMS OF OVEREXPOSURE.

=====
Fire Fighting Measures
=====

Flash Point:79F (T.C.C.)
Lower Limits:1.1

Upper Limits:6.6

Extinguishing Media:WATER FOG,DRY CHEMICAL,CO*2

Fire Fighting Procedures:USE NIOSH APPROVED SCBA FOR FIREFIGHTING IN
CONFINED SPACE

Unusual Fire/Explosion Hazard:FLAMMABLE LIQUID

=====
Accidental Release Measures
=====

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS. ELIM IGNITION
SOURCES. STOP LEAK. H*2O SPRAY COOL CONT/DIVERT SPILL FROM
FIRE/HEAT. PROVIDE VENTILATION. ABSORB W COMMERCIAL
ABSORBENT,SHOVEL INTO METAL DRUMS:LG
SPILL:DI KE W COMMERCIAL
ABSORBENT,PUMP INTO COVERED DRUMS.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP AWAY FROM FIRE SPARKS AND FLAME.
KEEP CONTAINER TIGHTLY CLOSED. STORAGE PER NFPA CLASS I C.

Other Precautions:DO NOT BREATH VAPORS. USE ADEQUATE VENTILATION. AVOID
SKIN AND EYES CONTACT.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR X

YLENE

Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN