View NSN Online: https://aerobasegroup.de/nsn/8010-00-597-8231

CORONADO PAINT CO INC -- ALKYD ENAMEL 123 -- 8010-00-597-8231

======== Product Identification ============

Product ID:ALKYD ENAMEL 123

MSDS Date:04/08/1992

FSC:8010

NIIN:00-597-8231

MSDS Number: BFHDG === Responsible Party ===

Company Name: CORONADO PAINT CO INC

Address:308 OLD COUNTRY RD

City:EDGEWATER

State:FL

ZIP:32032-1812 Country:US

Info Phone Num:904-428-6461

Emergency Phone Num:904-428-6461

Preparer's

Name:THOMAS E MAREK

CAGE:33200

=== Contractor Identification ===

Company Name: CORONADO PAINT COMPANY, INC.

Address:308 OLD COUNTY ROAD

Box:City:EDGEWATER

State:FL

ZIP:32132-1812 Country:US

Phone:904-428-6461

CAGE:33200

======= Composition/Information on Ingredients ========

Ingred Name:STODDARD SOLVENT (PETROLEUM DISTILLATE), MINERAL SPIRITS

CAS:8052-41-3

RTECS #:WJ8925000 Fraction by Wt: 40-50%

Other REC Limits:350 MG/CUM

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

Ingred Name:WEI

**GHT PER GALLON IN POUNDS: 3.9** RTECS #:9999999WG ========= Hazards Identification =============== Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: EYES: IRRITATION, REDNESS, TEARING, BLURRED VISION. SKIN: IRRITATION, DEFATTING, DERMATITIS. INHALATION: NASAL/RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, UNCONSCIOUSNESS & ASPHYXIATION. ION: GI IRRITATION, NAUSEA, VOMITING & DIARRHEA. ASPIRATION HAZARD. **Explanation of Carcinogenicity:NONE** First Aid:SKIN: WASH W/SOAP & WATER. EYES: FLUSH W/PLENTY OF WATER. INGESTION: DON'T INDUCE VOMITING. KEEP PERSON WARM. ASPIRATION INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. INHALATION: REMOV E TO FRESH AIR. IF BREATHING IS DIFFICULT. ADMINISTER OXGYEN. IF BREATHING HAS STOPPED, APPLY **ARTIFICIAL** RESPIRATION. KEEP PERSON WARM. OBTAIN MEDICAL ATTENTION IN ALL CASES. ============ Fire Fighting Measures ========================= Flash Point Method:SCC Flash Point:102F Lower Limits:1% **Upper Limits:6%** Extinguishing Media: FOAM, CO2, DRY CHEMICAL Fire Fighting Procedures: WEAR SCBA W/A FULL FACEPIECE OPERATED IN PRESSURE DEMAND OR OTHER POSITIVE PRESSURE MODE WHEN FIGHTING FIRES. Unusual Fire/Explosion Hazard: VAPORS ARE HEAVIER THAN AIR & MAY TRAVEL **ALONG** THE GROUND OR BE MOVED BY VENTILATION & IGNITE BY HEAT PILOT LIGHTS, FLAMES OR OTHER IGNITION SOURCES. ======== Accidental Release Measures ============= Spill Release Procedures: ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT OR OTHER ABSORBENT MATERIAL & PICK UP W/SHOVEL. ============ Handling and Storage =========================== Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS, OPEN

Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS, OPEN FLAME. USE W/ADEQUATE VENTILATION.

Other Precautions

| ====== Exposure Controls/Personal Protection ========  |
|--|
| Respiratory Protection:USE SELF CONTAINED NIOSH APPROVED RESPIRATOR IF TLV IS REACHED.  Ventilation:LOCAL EXHAUST AS NEEDED TO REMAIN BELOW PEL Protective Gloves:NEOPRENE OR NITRILE RUBBER Eye Protection:SAFETY GLASSES OR CHEMICAL GOGGLES Other Protective Equipment:BARRIER CREAM, EYE BATH, SAFETY SHOWER Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health |
| ========= Physical/Chemical Properties ==========  |
| HCC:F4 Boiling Pt:B.P. Text:300F Vapor Density:>1 Spec Gravity:1-1.2 Evaporation Rate & Description Rate & Reference:(ETHER = 1): 70 Solubility in Water:INSOLUBLE Appearance and Odor:WHITE OR COLORED OPAQUE LIQUID W/MINERAL SPIRITS ODOR. Percent Volatiles by Volume:59-64%   |
| ========= Stability and Reactivity Data =========  |
| Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS Stability Condition to Avo id:EXCESSIVE HEAT, SPARKS, OPEN FLAMES OR OTHER IGNITION SOURCES. Hazardous Decomposition Products:CO2 &/OR CO  |
| ======= Disposal Considerations ==========   |
| Waste Disposal Methods:INCINERATE UNDER SAFE CONDITIONS. DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS. COMBUSTIBLE LIQUID. UN1263.  |

:AVOID CONTACT W/SKIN.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. Th

e United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.