

AGS COMPANY (WAS AMERICAN GREASE STICK CO) -- LOCK-EASE, CAT#:LE-4 -- 9150-00-598-7122

=====
Product Identification
=====

Product ID:LOCK-EASE, CAT#:LE-4

MSDS Date:05/02/1994

FSC:9150

NIIN:00-598-7122

MSDS Number: BFHMM

=== Responsible Party ===

Company Name:AGS COMPANY (WAS AMERICAN GREASE STICK CO)

Address:2651 HOYT ST

Box:729

City:MUSKEGON HTS

State:MI

ZIP:49444

Country:US

Info Phone Num:800-2

53-0403

Emergency Phone Num:800-253-0403

Preparer's Name:TOMMY JONES

CAGE:96980

=== Contractor Identification ===

Company Name:AMERICAN GREASE STICK CO DBA AGS

Address:2651 HOYT ST

Box:729

City:MUSKEGON

State:MI

ZIP:49443

Country:US

Phone:231-733-2101; 800-253-0403

CAGE:96980

=====
Composition/Information on Ingredients
=====

Ingred Name:STODDARD SOLVENT (ALIPHATIC PETROLEUM NAPHTHA).

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 60-85%

Other REC Limits:NONE RECOMMENDED

OSH

A PEL:500 PPM
ACGIH TLV:100 PPM; 9394

Ingred Name:PETROLEUM OIL (PER MSDS SEVERELY HYDROTREATED OR SOLVENT REFINED).

Fraction by Wt: 5-15%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/CUM AS OIL MIST
ACGIH TLV:5 MG/CUM AS OIL MIST

Ingred Name:COLLOIDAL GRAPHITE DISPERSION

Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED
ACGIH TLV:5M3(OIL MIST)(MFG'S)

Ingred Name:ALUMINUM STEARATE BENZOATE COMPLEX

Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

=====
Hazard Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MAY CAUSE EYE IRRIT. MAY CAUSE SKIN IRRIT, DEFATTING, DERM. CONTAMINATED CLOTHING MAY CAUSE SEVERE IRRIT. MAY CAUSE GI IRRIT WHEN INGESTED. MAY CAUSE IRRIT OF RESP TRACT & CNS DEPRESSION WHEN INHALED. ASPIRATION INTO LUNGS MAY CAUSE CHEMICAL PNEUMONITIS.

Explanation of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER.

Effects of Overexposure:EYE/SKIN/RESP TRACT IRRIT. DERMATITIS. NAUSEA & VOMITING. CNS DEPRESSION. PNEUMONITIS DUE TO ASPIRATION INTO LUNGS.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MFG.

=====
First Aid Measures =====

First Aid:SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. INHALATION: REMOVE TO FRESH AIR & RESTORE BREATHING IF NECESSARY. GET MEDICAL AT

TENTION.

EYE : IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. INGESTION: GET IMMEDIATE MEDICAL ATTENTION. DO NOT INDUCE VOMITING. NOTHING BY MOUTH IF UNCONSCIOUS.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:>100F,>38C

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS. WATER FO

G MAY BE USED TO REDUCE VAPOR CONCENTRATION.

Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR AND ACCUMULATE IN LOW AREAS.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB WITH AN INERT MATERIAL.

Neutralizing Agent:NOT RELEVANT.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID EXCESSIVE HEAT.

Other Precautions:NONE SPECIFIED BY MFG.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESPIRATOR REQUIRED TO MAINTAIN CONCENTRATION BELOW TLV'S.

Ventilation:SUITABLE TO MAINTAIN CONCENTRATION BELOW TLV'S.

Protective Gloves:REQUIRED.

Eye Protection:REQUIRED.

Other Protective Equipment:EYE BATH IN WORK AREA.

Work Hygienic Practices:WASH HANDS AFTER HANDLING. WASH CONTAMINATED CLOTHING/SHOE PRIOR TO REUSE.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:F4

Vap

or Pres:UNK

Vapor Density:>1

Spec Gravity:0.81

Solubility in Water:NIL

Appearance and Odor:BLACK LIQUID WITH PETROLEUM ODOR

Percent Volatiles by Volume:85%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:NO

STRONG OXIDIZERS.

Stability Condition to Avoid:EXCESSIVE HEAT.

Hazardous Decomposition Products:DURING COMBUSTION MAY PRODUCE OXIDES
OF CARBON AND ALUMINUM.

===== Disposal Considerations =====

W

aste Disposal Methods:REMOVAL BY AN APPROVED LICENSED WASTE HAULER.

EPA WASTE ID NO:D001.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify
and

assume responsibility for the suitability of this information to their
particular situation.