

PRATT AND LAMBERT -- GLOSS GREEN 14187 -- 8010-00-616-7816

=====  
Product Identification  
=====

Product ID:GLOSS GREEN 14187

MSDS Date:01/01/1987

FSC:8010

NIIN:00-616-7816

MSDS Number: BFJBG

=== Responsible Party ===

Company Name:PRATT AND LAMBERT

Address:945 BURLINGTON

Box:206

City:KANSAS CITY

State:MO

ZIP:64141

Country:US

CAGE:92216

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT

INC

Address:945 BURLINGTON

Box:206

City:KANSAS CITY

State:MO

ZIP:64141

Country:US

CAGE:92216

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 40-5%

OSHA PEL:100 PPM

Ingred Name:TRIETHYLAMINE (SARA III)

CAS:121-44-8

RTECS #:YE0175000

Fraction by Wt: 0.5%

OSHA PEL:25 PPM/15 STEL

ACGIH TLV:10 PPM/15 STEL; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:LEAD CHROMATE

PIGMENT LD 50 VALUE GREATER THAN 10.000

GMS/KG

Fraction by Wt: 5-10%

Ingred Name:LIGHT CHROME GREEN LD 50 VALUE GREATER THAN 10 GMS/KG

=====  
===== Hazards Identification =====

Effects of Overexposure:INHALATION:ANESTHETIC,IRRITATION OF THE  
RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION CHARACT

=====  
===== First Aid Measures =====

First Aid:IN CASE OF CONTACT,FLUSH SKIN AND EYES WITH PLENTY OF WATER  
WHILE REMOVING  
CONTAMINATED CLOTHING.IF INHALED,REMOVE TO FRESH  
AIR.CALL A MD. IF SYMPTOMS PERSIST.

=====  
===== Fire Fighting Measures =====

Flash Point:104F

Extinguishing Media:USE NATIONAL FIRE PROTECTION ASSOC.(NFPA) CLASS B  
EXTINGUISH

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS SHOULD BE  
AVAILABLE FOR FI

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED.ISOLATE  
FROM HEAT,ELECTRICAL EQUIPMENT,SPARKS AND OPEN FLAME CLOSED

=====  
=====

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES,HOT  
SURFACES AND ELECTRICAL,STATIC,OR FRICTIONAL SPARKS)AVOID BREATHING  
VAPORS.VENTILATE AREA.REMOVE WITH INERT ABSORBENT AND NON-SPARKING  
TOOLS.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE  
QUANTITIES IN BUILDING DESIGNED TO COMPLY WITH OSHA 1910.106.

Other Precaution

s:CONTAINERS SHOULD BE GROUNDED WHEN POURING.AVOID FREE  
FALL OF LIQUID IN EXCESS OF A FEW INCHES.DO NOT FLAME CUT,BRAZE OR  
WELD COATED MATERIAL WITHOUT BUREAU OF MINES APPROVED RESPIRATOR OR  
APP

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN OUTDOOR OR OPEN AREAS,USE BUREAU OF MINES  
APPROVED MECHANICAL FIL

Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN  
VOL

Protective Gloves:REQUIRED FOR PR

Eye Protection:U

SE SAFETY EYEWEAR DESIGN

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO  
CONTAMINATED CLOTHING

Supplemental Safety and Health

INHALATION:ANESTHETIC,IRRITATIONOF THE RESPIRATORY TRACT OR ACUTE  
NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY  
HEADACHE,DIZZINESS,STAGGERING,GAIT,CONFUSION,UNCONSCIOUSNESS OR  
COMA.

===== Physical/Chemical Properties =====

HCC:F4

===== Stability and Reactivity Data =====

Stability Indicato

r/Materials to Avoid:YES

Stability Condition to Avoid:AVOID FIRES,HEAT AND HOT SURFACES.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL,STATE,AND  
FEDERAL REGULATIONS. INCINERATE IN APPROVED FACILITY. DO NOT  
INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States o

f America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.