View NSN Online: https://aerobasegroup.com/nsn/8010-00-616-9181

Product ID:TT-P-605, PRIMER COATING, ALKYD, GRAY MSDS Date:01/01/1987 FSC:8010 NIIN:00-616-9181 MSDS Number: BFJBV === Responsible Party === Company Name: BULK CHEMICALS DIST., INC. Emergency Phone Num:504-362-3232 CAGE:56921 === Contractor Identification === Company Name: BULK CHEMICA LS DISTRIBUTORS, INC Address:80 FIRST STREET City:GRETNA, State:LA ZIP:70053 Country:US Phone:504-362-3232 DISCONNECTED(2-20-92) CAGE:56921

Ingred Name: ALKYD RESIN (ACCORDING TO FEDERAL SPECIFICATION TT-P-605)

Ingred Name:SOLVENTS (SEE SUPPLEMENTAL DATA FOR ADDITIONAL INFORMATION) ACGIH TLV:100 PPM (MFR)

Ingred Name:LAMP BLACK (ACCORDING TO FEDERAL SPECIFICATION TT-P-605) (SEE SUPP DATA) RTECS #:FF5250000

Ingred Name:PR OPANE/ISOBUTANE (APPROXIMATELY 25% OF THE PRODUCT ACCD TO THE MFR) PHONECON 1/15/87

Ingred Name: ADDITIVES

Effects of Overexposure:INH:ANESTHETIC,HEADACHE,NAUSEA,DIZZINESS. LIQ MODERATELY IRRITATING TO SKIN & EYES.

First Aid:INH:REMOVE VICTIM & RESTORE BREATHING IF NECESSARY. SKIN:REMOVE FROM SKIN W/SOAP & WATER.EYES:FLUSH W/COPIOUS QUANTITES OF WATER FOR 15 MIN. SEE A PHYSICIAN.

Flash Point:80F TCC Lower Limits:1.0 Upper Limits:7.0 Extinguishing Media:CO*2,DRY CHEMICAL OR FOAM Fire Fighting Procedures:WEAR SCBA.USE WATER TO COOL CLSD CANS,PREVENT PRESS BUILD UP Unusual Fire/Explosion Hazard:KEEP CANS TIGHTLY CLSD.KEEP FROM ALL IGNIT SOURCES.CLSD CANS MAY EXPLO FRM EXTRM HEAT AVOID HOT SURF

=====

Spill Release Procedures:WIPE UP IMMEDIATELY & SAFELY DISCARD SATURATED ABSORBENTS. IN CASE OF LARGE SPILLS, DIKE AREAS & PUMP MATERIAL TO A WASTE TANK. MAINTAIN SUFFICIENT VENTILATION.

Handling and Storage Precautions:DO NOT STORE ABOVE 120F,STORE LARGE QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS II FLAMMABLE LIQ.DO NOT STORE NEAR FEED/FOOD PRODUCTS.
Other Precautions:MFR STATES PRODUCT HA
S NOT BEEN SOLD BY TEM IN APPROXMATELY 5 YEARS.

Respiratory Protection:NIOSH/MSHA APPRVD RESP;MFR RECM MECH FILTER RESP;CONSULT SAFETY/I.H.

Ventilation:LOC EXHST:CONTROL BELOW TLV.SPECIAL:APPROVED CHEM-MECH RESP.

Protective Gloves: FOR PRLNGD USE

Eye Protection:SAFETY GLASSES FOR SPLASH

Other Protective Equipment: PREVENT PROLONGED SKIN CONTACT

W/CONTAMINATED CLOTHING

Supplemental Safety and Health HAZ INGRED:POC

W/BULK CHEMICALS (TY CASEBONNE) OF 1/15/87 STATES SOLVENTS PROBABLY INCLUDE METHYLENE CHLORIDE & XYLENE; PIGMENTS PROBABLY INCLUDE TI0*2. DECOMP PRODUCTS MAY INCLUDE HCL, PHOSGENE

HCC:F4 Boiling Pt:B.P. Text:279-289F Vapor Pres:9.5 Vapor Density:>1.0 Spec Gravity:1.23 Evaporation Rate & amp; Reference:SLOWER THAN ETHER Solubility in Water:INSOLUBLE Appearance and Odor:GRAY-AROMATIC ODOR (NAPHTHA) Percent Volatiles by Vo lume:52.5

Stability Indicator/Materials to Avoid:YES WATER,EXCESS ALIPHATIC SOLVENT Stability Condition to Avoid:FLAME,HIGH HEAT,MOISTURE Hazardous Decomposition Products:SEE SUPP DATA. MAY EMIT ACRID FUMES FROM THE LIQUID. Conditions to Avoid Polymerization:EXCESSIVE HEAT & MOISTURE

Waste Disposal Methods:DISPOSE OF IAW LOCAL,STATE & FEDERAL REGULAT IONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of t his information to their particular situation.