

PRODUCTS RESEARCH & CHEMICAL CORP -- PR-1201-RLS -- 8030-00-631-8013

===== Product Identification =====

Product ID:PR-1201-RLS

MSDS Date:01/01/1985

FSC:8030

NIIN:00-631-8013

MSDS Number: BFJNN

=== Responsible Party ===

Company Name:PRODUCTS RESEARCH & CHEMICAL CORP

Address:5430 SAN FERNANDO ROAD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Info Phone Num:818-240-2060

Emergency Phone Num:8

18-240-2060

CAGE:DO563

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

Company Name:PRODUCTS RESEARCH & CHEMICAL

Address:NOW DBA COURTAULDS AEROSPACE

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Phone:818-240-2060

CAGE:DO563

===== Composition/Information on Ingredients =====

Ingred Name:LEAD PEROXIDE (LEAD DIOXIDE)

, (OSHA PEL FROM 29CFR  
1910.1025)  
CAS:1309-60-0  
RTECS #:OG0700000  
Fraction by Wt: 7%  
OSHA PEL:0.05 MG/M3 (PB)  
ACGIH TLV:0.15 MG/M3(PB); 8990

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 5%  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

=====  
Hazards Identification  
=====

Effects of Overexposure:BASE COMPD MAY BE SKIN IRRITNT.CATALYST  
CONTAINS LEAD WHICH MAY BE ABSORBED THROUG  
H SKIN.

=====  
First Aid Measures  
=====

First Aid:SKIN:WASH THOROUGHLY WITH SOAP & WATER.EYES:WASH OUT  
THOROUGHLY WITH LARGE AMOUNTS OF WATER.SEE A  
PHYSICIAN.INGESTION:INDUCE VOMITING.INHALATION:REMOVE TO FRESH  
AIR.GIVE CPR/OXYGEN IF NECESSARY.

=====  
Fire Fighting Measures  
=====

Flash Point:92F/33.3C PMCC  
Lower Limits:1.0  
Upper Limits:7.0  
Extinguishing Media:FOAM,DRY CHEMICAL,CARBON DIOXIDE  
Fire Fighting Proce  
dures:WEAR SELF-CONTND BRTHG APPARATUS WHEN FIGHTING  
FIRES.  
Unusual Fire/Explosion Hazard:EMISSION OF TOXIC VAPORS.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:STOP LEAK.ELIMINATE IGNITION SOURCES.KEEP  
UNPROTECTED PERSONS FROM HAZARD AREA.ABSORB EXCESS WITH RAGS,PAPER  
TOWELS.CLEAN AREA WITH TOLUENE OR XYLENE.PLACE IN CLOSED  
CONTAINERS.

=====  
Handling and Storage  
=====

Handling and Storage Prec

autions:KEEP IN CLOSED CONTAINERS AT ROOM  
TEMPERATURE.AVOID ACCELERATOR SPILLAGE.AVOID FIRE HAZARDS.PROTECT  
FROM PHYSICAL DAMAGE.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:AIR SUPPLIED RESPIRATOR RECOMMENDED IN CONFINED  
AREAS.

Ventilation:MECHANICAL/LOCAL EXHAUST ADEQUATE TO MINIMIZE SOLVENT  
VAPOR

Protective Gloves:POLYETHYLENE

Eye Protection:SAFETY GLASSES

Other Protective Equipment:USE PROTECTIVE HAND CREAM

Supplemental Safety  
and Health

PER CENT VOLATILE BY VOLUME IS 6%.

=====  
===== Physical/Chemical Properties =====

HCC:F2

Vapor Pres:UNK

Vapor Density:UNK

Spec Gravity:1.62

Solubility in Water:NEGLIGIBLE

Appearance and Odor:PINKISH BROWN,THICK LIQUID,SLIGHT TOLUENE ODOR

Percent Volatiles by Volume:6

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

DECOMPOSES WHEN EXPOSED TO STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:AV

OID HEAT SOURCES

Hazardous Decomposition Products:OXIDES OF SULFUR;HYDROGEN  
SULFIDE;FORMIC ACID

=====  
===== Disposal Considerations =====

Waste Disposal Methods:PLACE IN CLOSED CONTAINERS AND DISPOSE IN  
ACCORDANCE WITH LOCAL,FEDERAL AND STATE REGULATIONS.DO NOT  
INCINERATE.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America

in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.