

DEVOE MARINE COATING CO -- FORMULA 122-27,NO. 27 HAZE GRAY,MIL-E-15936 --
8010-00-634-7324

===== Product Identification =====

Product ID:FORMULA 122-27,NO. 27 HAZE GRAY,MIL-E-15936

MSDS Date:01/01/1985

FSC:8010

NIIN:00-634-7324

MSDS Number: BFJPX

=== Responsible Party ===

Company Name:DEVOE MARINE COATING CO

Address:4000 DUPONT CIRCLE

City:LOUISVILLE

State:KY

ZIP:40207-4802

Country:US

CAGE:EO141

=== Contractor Identification ===

Company Name:DEVOE MARINE COATING CO.

Address:4000 DUPONT CIRCLE

Box:7600

City:LOUISVILLE

State:KY

ZIP:40207-4802

Country:US

Phone:502-897-9861

CAGE:EO141

Company Name:GROW GROUP INC DEVOE AND REYNOLDS CO DIV

Address:4000 DUPONT CIRCLE

Box:City:LOUISVILLE

State:KY

ZIP:40207-4802

Country:US

Phone:502-361-2536

CAGE:97758

===== Composition/Information on Ingredients =====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE

2100000
Fraction by Wt: 10%
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 40%
OSHA PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
Hazards Identification
=====

Effects of Overexposure:SKIN/EYE: IRRITATION. INHALATION: IRRIT OF RESP
TRACT,HEADACHE,HAUSEA,DIZZINE
SS.

=====
First Aid Measures
=====

First Aid:EYE: FLUSH WITH WATER 15 MIN,CALL A MD. SKIN: FLUSH
W/WATER,REMOVE CONTAMINATED CLOTHING. INHALATION: MOVE TO FRESH
AIR. INGESTION: CALL MD IMMEDIATELY

=====
Fire Fighting Measures
=====

Flash Point:70F/21C (PMCC)
Lower Limits:1.1
Extinguishing Media:CO*2,DRY CHEMICAL,FOAM
Fire Fighting Procedures:SELF-CONT BREATH APP,WATER FOG TO COOL EXPOSED
CONTAINERS.
Unusual F
ire/Explosion Hazard:DUE TO PRESSURE BUILD-UP,CLOSED
CONTAINERS EXPOSED TO HEAT MAY EXPLODE.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID
BREATHING VAPORS. VENT AREA. CONTAIN SPILLED MATERIAL AND REMOVE
WITH INERT ABSORBENT AND NON-SPARKING TOOLS. STORE IN CLOSED
CONTAINER UNTIL PROPERLY DISPOSED OF .

=====
Handling and Storage
=====

Handling and Storage Pr

Precautions: DONOT STORE ABOVE 120F/48C OR OPEN
FLAME. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED TO COMPLY WITH
OSHA 1910.106.

Other Precautions: CLOSE CONTAINERS AFTER USE. DO NOT REUSE EMPTY
CONTAINERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH
EXPOSURE OF CONCERN
Ventilation: GENERAL DILUTION/LOCAL EXHAUST WITH EXPLOSION PROOF MOTORS
Protective Gloves: SOLVENT RESIST
Eye Protection:
EYEWEAR, SOLVENT RESISTANT
Other Protective Equipment: NORMAL PROTECTIVE CLOTHING.
Supplemental Safety and Health
PKG 5 GAL, MFR ID CODE: FORMULA 122-27, MIL-P-15936, MD-8913

===== Physical/Chemical Properties =====

HCC: F2
Boiling Pt: B.P. Text: 240F/115C
Vapor Density: >1
Evaporation Rate & Reference: SLOWER THAN ETHER
Percent Volatiles by Volume: 70

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
OXIDIZING MATERIALS, RUBBER SOFTENS.
Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE, OXIDES
OF NITROGEN

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE &
FEDERAL REGULATIONS. INCINERATE ONLY IN APPROVED FACILITY. DO NOT
INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.