

INDUSTRIAL RUBBER CEMENT CO. -- LOCK BOND -- 8040-00-656-0929

===== Product Identification =====

Product ID:LOCK BOND

MSDS Date:01/01/1987

FSC:8040

NIIN:00-656-0929

MSDS Number: BFJZZ

=== Responsible Party ===

Company Name:INDUSTRIAL RUBBER CEMENT CO.

Emergency Phone Num:213-333-4578

CAGE:55913

=== Contractor Identification ===

Company Name:INDUSTRIAL RUBBER CEMENT CO

Address:15257 E PROCTOR AVE

Box:City:CITY OF INDUSTRY

State:CA

ZIP:91745-1019

Country:US

CAGE:55913

===== Composition/Information on Ingredients =====

Ingred Name:SOLVENTS

Ingred Name:ETHYL ALCOHOL (ETHANOL)

CAS:64-17-5

RTECS #:KQ6300000

Fraction by Wt: 10%

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

Ingred Name:MINERAL SPIRITS

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 5%

ACGIH TLV:500

===== Hazards Identification =====

Effects of Overexposure:ESSENTIALLY IDEN

TICAL TO GASOLINE IN IRRITATIVE  
& NARCOTIC ACTION

=====  
First Aid Measures  
=====

First Aid:INHALATION-REMOVE TO FRESH AIR. SKIN CONTACT-WASH  
W/ALCOHOL-FOLLOWED BY SOAP & WATER. EYE CONTACT-FLOOD W/LARGE  
QUANTITIES OF WATER. INGESTION-DO NOT INDUCE VOMITING. CALL  
PHYSICIAN IMMEDIATELY.

=====  
Fire Fighting Measures  
=====

Flash Point:NONE  
Extinguishing Media:CO\*2 & FINE SPRAY WATER

=====  
Accid  
ental Release Measures  
=====

Spill Release Procedures:MATERIAL IS VERY VISCOUS & WILL NOT FLOW FROM  
OPEN CONTAINER. PICK UP W/SPATULA OR TROWEL.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:USE WITH ADEQUATE VENTILATION;STORE AT  
ROOM TEMPERATURE-OUT OF DIRECT SUNLIGHT IN VENTILATED AREA.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:NOT NORMALLY REQUIRED  
Ventilation:LOC  
EXHAUST-GENERAL DILUTION VENTILATION SPECIAL-SUFFICIENT  
Protective Gloves:KEEP OFF SKIN  
Supplemental Safety and Health

=====  
Physical/Chemical Properties  
=====

HCC:N1  
Boiling Pt:B.P. Text:173F 78C  
Spec Gravity:1.38  
Evaporation Rate & Reference:N-BU OAC 3.2  
Solubility in Water:NEGLIGIBLE  
Percent Volatiles by Volume:10

=====  
Stability and Reactivity Data  
=====

Stability Indicator/Materials to Avoid:YES  
Stability Condition to Avoid:DIRE

CT EXPOSURE TO HEAT OR FLAME

Hazardous Decomposition Products:EMITS DENSE ACRID SMOKE

===== Disposal Considerations =====

Waste Disposal Methods:REPLACE TO SEALED CONTAINER, LANDFILL. REFER TO LOCAL DISPOSAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrant

s this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.