

FISKE BROTHERS REFINING CO -- LUBRIPLATE "600" SERIES, P/N 600-AA -- 9150-00-663-1770  
===== Product Identification =====

Product ID:LUBRIPLATE "600" SERIES, P/N 600-AA

MSDS Date:11/01/1985

FSC:9150

NIIN:00-663-1770

MSDS Number: BFKFN

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:8038

City:TOLEDO

State:OH

ZIP:43605-3843

Country:US

Info Phone Num:419

-691-2491

Emergency Phone Num:419-691-2491

Preparer's Name:O.F.KUHLMAN

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

Company Name:OHIO TRANSMISSION AND PUMP CO

Address:666 PARSONS AVE

Box:City:COLUMBUS

State:OH

ZIP:4320

6-1435  
Country:US  
Phone:614-444-3172  
CAGE:8A634

=====  
Composition/Information on Ingredients  
=====

Ingred Name:LITHIUM SOAP  
Other REC Limits:NONE SPECIFIED

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')  
CAS:8012-95-1  
RTECS #:PY8030000  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:5 MG/M3  
ACGIH TLV:5 MG/M3/10 STEL;9293

Ingred Name:ADDITIVES  
Other REC Limits:NONE SPECIFIED

=====  
Hazards Identification  
=====

LD50 LC50 Mixture:ORAL LD5  
0 (RAT) IS UNKNOWN.  
Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYES: MAY CAUSE IRRITATION. SKIN:  
PROLONGED OR REPEATED CONTACT MAY CAUSE IRRITATION. HIGH PRESSURE  
INJECTION MAY CAUSE LOCAL NECROSIS. INHALATION: NOT EXPECTED TO BE  
A RELEVANT ROUTE OF EXPOSURE. HIGH TEMPERATURE VAPORS MAY CAUSE  
IRRITATION OF RESPIRATORY TRACT. INGESTION: PRODUCT HAS A LOW ORDER  
OF ACUTE TOXICITY.  
Effects of Overexposure:EYES; IRRITATION. SKIN: IRRITATION, LOCAL  
NECROSIS. INHALATION: NOT EXPECTED TO BE A RELEVANT ROUTE OF  
EXPOSURE. INGESTION: PRODUCT HAS LOW ORDER OF ACUTE TOXICITY.  
Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS MAY BE  
AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

=====  
First Aid Measures  
=====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER. IF IRRITATION  
PERSISTS, GET MEDICAL ATTENTION. SKIN: REMOVE CO

NTAMINATED

CLOTHING. WASH AREA WITH SOAP AND WATER. IF INJECTED UNDER SKIN, GET MEDICAL ATTENTION . INHALATION: NOT A PROBLEM AT ROOM TEMPERATURE. IF OVERCOME BY VAPOR FROM HOT PRODUCT, MOVE TO FRESH AIR. GET MEDICAL ATTENTION. INGESTION: GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:400F,204C

Lower Limits:0.9

Upper Limits:7.0

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE, OR WATER SPRAY.

Fire Fighting Procedures:USE WATER SPRAY TO COOL FIRE EXPOSED

CONTAINERS. USE AIR-SUPPLIED RESCUE EQUIPMENT FOR ENCLOSED AREAS.

Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS.

EMPTY CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GRIND, WELD, AS THEY MAY EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP GREASE, WASH REMAINDER WITH SUITABLE PETROLEUM SOLVENT OR ADD ABSORBENT. KEEP PETROLEUM PRODUCT

TS OUT OF

SEWERS AND WATER COURSES. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTER SEWERS AND WATER COURSES.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA AWAY FROM HEAT, SPARKS, FLAME, OR STRONG OXIDANTS. KEEP CONTAINER CLOSED WHEN NOT IN USE.

Other Precautions:MINIMIZE SKIN CONTACT. AVOID BREATHING OIL MIST.

=====

== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation:NORMAL ROOM VENTILATION. USE LOCAL EXHAUST TO CAPTURE FUMES AND VAPORS CLOSE TO THE SOURCE.

Protective Gloves:USE OIL RESISTANT GLOVES IF NEEDED.

Eye Protection:WEAR GOGGLES IF CHANCE OF EYE CONTACT.

Other Protective Equipment:USE OIL RESISTANT APRON, IF NEEDED.

Work Hygienic Practices:WASH AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHI

NG BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>550F/>288C

Vapor Pres:5

Spec Gravity:0.94 - 0.95

Evaporation Rate & Reference: