

PLASTI-KOTE CO, INC -- X8361 -- 8010-00-664-1914

=====
Product Identification
=====

Product ID:X8361

MSDS Date:01/01/1985

FSC:8010

NIIN:00-664-1914

MSDS Number: BFKMC

=== Responsible Party ===

Company Name:PLASTI-KOTE CO, INC

Emergency Phone Num:216-725-4511

CAGE:FO468

=== Contractor Identification ===

Company Name:PLASTI-KOTE CO, INC

Address:1000 LAKE ROAD

City:MEDINA

State:OH

ZIP:44256

Phone:(2

16) 725-4511

CAGE:FO468

Company Name:TEMPO PRODUCTS CO A PLASTI-KOTE CO INC

Address:1000 LAKE ROAD

Box:City:MEDINA

State:OH

ZIP:44256

Country:US

Phone:330-725-4511

CAGE:07708

=====
Composition/Information on Ingredients
=====

Ingred Name:ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 24.8%

OSHA PEL:1000PPM

ACGIH TLV:750PPM/1000STEL;9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL ALCOHOL

RTECS #:KJ5075000

Fraction by Wt: 1.3%

ACGIH TLV:1000

PPM

Ingred Name:ETHYL ACETATE
RTECS #:KQ4900000
Fraction by Wt: 1.3%
ACGIH TLV:400 PPM

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 3.5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM
ACGIH TLV:200 PPM/300STEL;9394
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 1.4%
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

=====
= Hazards Identification =====

Effects of Overexposure:BREATHING-NASAL & RESP. IRRIT.,DIZZINESS,ETC.
INGEST-GASTROINTESTINAL IRRIT.; NAUSEA & DIARRHEA.

=====
===== First Aid Measures =====

First Aid:INGEST-DO NOT INDUCE VOMITING;KEEP WARM & QUIET;GET MED AID
ASPIRATION INTO LUNGS MAY CAUSE PNEUMONITIS WHICH CAN BE FATAL.
BREATH-REMOVE TO FRESH AIR, IF NEC ADMINISTER OXYGEN OR ARTIFICIAL
RESP. KEE P WARM & QUIET. GET MED AID.

=
===== Fire Fighting Measures =====

Flash Point:0F,-18C CC
Extinguishing Media:CO2, DRY CHEM, ALCOHOL FOAM
Fire Fighting Procedures:WATER MAY BE INEFFECTIVE.USE TO COOL CLOSED
CONTAINERS.
Unusual Fire/Explosion Hazard:VAPORS HEAVIER THAN AIR MAY BE MOVED
ALONG FLOOR BY DRAFTS TO DISTANT SOURCES OF IGNITION.

=====
===== Accidental Release Measures =====

Spill Release Procedures:ABSORB ON PAPER, VERMICULITE FLOOR ABSORBENT
OR O

OTHER ABSORBENT MAT'L & TRANSFER TO CLOSED CONTAINER. ELIMINATE ALL IGNITION SOURCES.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE OVER 120F OR IN DIRECT SUNLIGHT OR NEAR HEAT OR OPEN FLAME

Other Precautions:STORE LGE QTY'S IN NFPA CLASS IC FLAMMABLE LIQUIDS BLDG.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:ABOVE TLV USE NIOSH/MESA SELFCONTAINED BREATH APPAR/POSITIVE PRESSURE

IVE PRESSURE

Ventilation:MECH OR LOCAL TO MAINTAIN EXPOSURE BELOW TLV

Protective Gloves:CHEM RESISTANT

Eye Protection:SPLASH GOGGLE

Supplemental Safety and Health

N-BUTANOL, TOLUOL, XYLOL, DIACETONE ALCOHOL, METHYL ISOBUTYL KETONE

=====
Physical/Chemical Properties
=====

HCC:F2

Boiling Pt:B.P. Text:133-331F

Vapor Density:>AIR

Evaporation Rate & Reference: