

TEXACO INC. -- 1567 CAPELLA OIL WF 32 -- 9150-00-664-4447

===== Product Identification =====

Product ID:1567 CAPELLA OIL WF 32

MSDS Date:01/01/1985

FSC:9150

NIIN:00-664-4447

MSDS Number: BFKNY

=== Responsible Party ===

Company Name:TEXACO INC.

Emergency Phone Num:914-831-3400 X406

CAGE:38431

=== Contractor Identification ===

Company Name:DIGITAL CONTROL SYSTEMS INC

Address:3160 GRAND MARAIS E

Box:

City:WINDSOR, N8W 4W5

State:ON

Country:CN

Phone:NONE

CAGE:38431

Company Name:TEXACO INC CORPORATE HQ

Address:2000 WESTCHESTER AVE

City:WHITE PLAINS

State:NY

ZIP:10604

Country:US

Phone:914-253-4000

CAGE:59595

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

Fraction by Wt: 100%

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

===== Hazards Identification =====

=====

Effects of Overexposure:EYES & SKIN: MILD IRRIT. INH: MILD IRRIT IF NOT  
IN EXCESS OF PERMISSIBLE CONCENTRATIONS.

===== First Aid Measures =====

First Aid:EYES: FLUSH W/ PLENTY OF WATER FOR 15 MINUTES. SKIN: WASH W/  
SOAP AND WATER, SEVERAL TIMES DAILY. INH: REMOVE FROM EXPOSURE.

===== Fire Fighting Measures =====

Flash Point:330F;166C (COC)  
Extinguishing Media:WATER SPRAY, DRY CHEMICAL, ALCOHOL FOAM, CO\*  
2  
Fire Fighting Procedures:USE H\*2O TO COOL FIRE-EXPOSED CANS.  
Unusual Fire/Explosion Hazard:WATER OR FOAM MAY CAUSE FROTHING. CO,  
CO\*2, ALDEHYDES, KETONES AND COMBUSTION PROD OF N AND S FORM.

===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN SPILL. ABSORB W/ INERT POROUS  
MATERIAL. IF A LEAK OR SPILL HAS NOT IGNITED, USE WATER SPRAY TO  
DISPERSE VAPORS AND TO PROVIDE PROTECTION FOR PERSONS ATTEMPTING TO  
STOP THE LEAK.

=====

===== Handling and Storage =====

Other Precautions:EXERCISE REASONABLE PERSONAL CLEANLINESS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED IF EXPOSURE WITHIN PERMISSIBLE  
CONCENTRATIONS (MFR)  
Ventilation:NORMAL- TO KEEP BELOW TLV.  
Eye Protection:GOGGLES/FACE SHIELD  
Other Protective Equipment:LAUNDER SOILED WORK CLOTHING.  
Supplemental Safety and Health  
CONTAINER SIZE: 1.0 QT. SPEC: TYPE I. VAPOR PRESSURE &

% VOLATILE BY  
VOLUME: NIL. N/D=NOT DETERMINED.

===== Physical/Chemical Properties =====

HCC:V6  
Boiling Pt:B.P. Text:546F;286C  
Spec Gravity:0.898  
Evaporation Rate & Reference:N/D  
Solubility in Water:INSOLUBLE  
Appearance and Odor:CLEAR PALE YELLOW

===== Stability and Reactivity Data =====

Hazardous Decomposition Products:CO,CO\*2,ALDEHYDES,KETONES,COMBUSTION  
PROD OF N AND S.

===== Disposal Considerations =====  
=====

Waste Disposal Methods:MFR RECOMMENDS: DISPOSE AS AN OILY WASTE.  
CONTACT A WASTE OIL CONTRACTOR OR DISPOSAL SPECIALIST IF NECESSARY.  
DISPOSAL METHOD MUST BE IAW FEDERAL, STATE AND LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disc  
laims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.