

DAVIS-HOWLAND OIL CORPORATION -- VV-L-825A,TYPE 3 -- 9150-00-664-4448

=====
Product Identification
=====

Product ID:VV-L-825A,TYPE 3

MSDS Date:01/01/1985

FSC:9150

NIIN:00-664-4448

MSDS Number: BFKPB

=== Responsible Party ===

Company Name:DAVIS-HOWLAND OIL CORPORATION

Emergency Phone Num:(716)473-6650

CAGE:FO626

=== Contractor Identification ===

Company Name:DAVIS HOWLAND OIL CORP.

Address:200 AND

ERSON AVE.

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Phone:716-473-6650

CAGE:5A565

Company Name:DAVIS-HOWLAND OIL CORPORATION

Address:200 ANDERSON AVENUE

City:ROCHESTER

State:NY

ZIP:14607

Phone:(716) 473-6650

CAGE:FO626

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM HYDROCARBONS (ACGIH TLV CAN BE USED AS OIL MIST
5MG/CUM)

Fraction by Wt: 100%

=====
Hazards Identification
=====

Effects of Overexposure:PROLONG

ED OR REPEATED SKIN CONTACT MAY CAUSE
MILD SKIN IRRITATION.

=====
First Aid Measures
=====

First Aid:IN CASE OF SKIN CONTACT,WASH WITH SOAP & WATER IF SPLASHED
INTO EYES,FLUSH WITH CLEAR WATER UNTIL IRRITATION SUBSIDES.

=====
Fire Fighting Measures
=====

Flash Point:475F(C.O.C.)

Lower Limits:1.0

Upper Limits:7.0

Extinguishing Media:CO*2, FOAM, DRY CHEM & H*2O FOG.

Fire Fighting Procedures:USE AIR-SUPPLIED RESCUE E
QUIPMENT FOR ENCLOSED
AREAS.

Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS

=====
Accidental Release Measures
=====

Spill Release Procedures:RECOVER FREE LIQUID.ADD ABSORBENT TO SPILL
AREA. KEEP PETROLEUM PRODUCTS OUT OF STREAMS & WATER-WAYS.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED. KEEP AWAY FROM
HEAT & OPEN FLAMES.

Other Precautions:AVOID BREAT

HING OF OIL MIST. REMOVE OIL IMPREGNATED
CLOTHING.WASH THOROUGHLY AFTER/EXPOSURE.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NO SPECIAL REQMENTS UNDER ORDINARY
CONDITIONS/ADEQUATE VENT.

Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN